1407619

https://www.phoenixcontact.com/us/products/1407619

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, B6, for single locking latch, height: 60.5 mm, without EVO screw connection

Your advantages

- · Flexible cable outlet direction, lateral or straight
- · Lower costs than metal version
- · Low weight
- · Lower risk of condensation

Commercial data

Item number	1407619
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF57
Product key	BF7APL
Catalog page	Page 598 (C-2-2019)
GTIN	4046356776813
Weight per piece (including packing)	59.7 g
Weight per piece (excluding packing)	58.2 g
Customs tariff number	85389099
Country of origin	PL

PHŒNIX

1407619

https://www.phoenixcontact.com/us/products/1407619



Technical data

Notes

	General	For contact inserts HC-B6, BB10, DD24, M	
Pro	Product properties		
	Туре	B6	
	Product type	Housing with locking latch	
	Product family	HC-EVO-B	
	Application	Standard	
	No. of cable outlets	1	
	Housing type	Sleeve housing	
	Cable outlet	straight	
	Pg screw connection	none	

Dimensions

Dimensional drawing	
Width	49 mm
Height	60.5 mm
Length	60 mm

Material specifications

Flammability rating according to UL 94	V0 (Housing)
Impact strength	IK08
Housing material	PA

Mechanical properties

Me	chanical data	
l	Locking type	Pin

Mounting

Assembly instructions	The sleeve base housing must be supplemented with the EVO
Assembly instructions	o 11
	screw connection. The EVO screw connection is available in four
	sizes. It facilitates the creation of a straight or a side cable outlet.
	The EVO screw connection is mounted with the aid of, for
	example, a pipe wrench

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP66



https://www.phoenixcontact.com/us/products/1407619

Enclosure rating (NEMA)	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C



1407619

https://www.phoenixcontact.com/us/products/1407619



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

	ETIM 9.0	EC000437
UN	ISPSC	
	UNSPSC 21.0	31261500



1407619

https://www.phoenixcontact.com/us/products/1407619



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com