


# SAC-6P-10,0-PURMC/M12FR - Master cable



1407821

<https://www.phoenixcontact.com/us/products/1407821>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M12 socket, angled, 6-pos., with connected master cable, for sensor/actuator box with M8 slots, cable length: 10 m

## Commercial data

Item number	1407821
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF03
Product key	BF1CFA
Catalog page	Page 311 (C-2-2019)
GTIN	4046356857499
Weight per piece (including packing)	344.8 g
Weight per piece (excluding packing)	330 g
Customs tariff number	85444290
Country of origin	PL

# SAC-6P-10,0-PURMC/M12FR - Master cable



1407821

<https://www.phoenixcontact.com/us/products/1407821>

## Technical data

### Product properties

Product type	Master cable, assembled
Number of positions	6
Application	Sensor/actuator box
Number of slots	4
Coding	A

### Electrical properties

Nominal voltage $U_N$	30 V AC
	30 V DC

### Connection data

Connection method	Fixed connection
-------------------	------------------

### Signaling

Status display present	No
------------------------	----

### Material specifications

Material Housing	PUR
Material Threaded sleeve	Cu alloy
Flammability rating according to UL 94	HB
Seal material	NBR
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF

### Connector


#### Connection 1

Coding type	A
-------------	---

### Cable/line

Cable length	10 m
--------------	------

#### PUR halogen-free black [PUR]

Dimensional drawing	
---------------------	--

# SAC-6P-10,0-PURMC/M12FR - Master cable



1407821

<https://www.phoenixcontact.com/us/products/1407821>

Cable weight	34 kg/km
Number of positions	6
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	6x 0.25 mm <sup>2</sup> (Signal line)
Wire diameter incl. insulation	1.17 mm ±0.02 mm
External cable diameter	5.00 mm 5.00 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material, filler	PE
Material wire insulation	PP
Single wire, color	brown, white, blue, black, gray, pink
Thickness, insulation	≥ 0.21 mm (Core insulation)
Thickness, outer sheath	approx. 0.70 mm
Overall twist	Six cores around the filler to the core
Max. conductor resistance	78 Ω/km (at 20 °C)
Insulation resistance	≥ 100 MΩ*km (at 20 °C)
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 3000 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Smallest bending radius, fixed installation	25 mm
Smallest bending radius, movable installation	50 mm
Halogen-free	in accordance with DIN VDE 0472 part 815
Flame resistance	in accordance with DIN UL-Style 20549
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)
Special properties	Flexible cable conduit capable Silicone-free Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65 IP67
----------------------	--------------

# SAC-6P-10,0-PURMC/M12FR - Master cable



1407821

<https://www.phoenixcontact.com/us/products/1407821>

	IP68
Ambient temperature (operation)	-25 °C ... 80 °C (Plug / socket)

## Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

# SAC-6P-10,0-PURMC/M12FR - Master cable



1407821

<https://www.phoenixcontact.com/us/products/1407821>

## Classifications

### ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

### ETIM

ETIM 9.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SAC-6P-10,0-PURMC/M12FR - Master cable



1407821

<https://www.phoenixcontact.com/us/products/1407821>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)