

# HC-COM- 8-EBUC - Contact insert



1408494

<https://www.phoenixcontact.com/us/products/1408494>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert, number of positions: 8+PE, size: COM, power contacts: 8, control contacts: 0, number of connections per position: 1, Socket, Crimp connection, 500 V, 16 A, 0.5 mm<sup>2</sup> ... 4 mm<sup>2</sup>, application: Power

## Product description

Contact insert, incl. 4 mounting screws

## Commercial data

Item number	1408494
Packing unit	2 pc
Minimum order quantity	2 pc
Sales key	BF61
Product key	BF7ABH
Catalog page	Page 649 (C-2-2017)
GTIN	4046356618205
Weight per piece (including packing)	16.4 g
Weight per piece (excluding packing)	16.35 g
Customs tariff number	85389099
Country of origin	CN

# HC-COM- 8-EBUC - Contact insert



1408494

<https://www.phoenixcontact.com/us/products/1408494>

## Technical data

### Notes

General	For crimp contacts CK2,5-ED...
General	Connectors may be operated only when there is no load/voltage.

### Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
-----------------------	---


### Product properties

Type	COM
Product type	Contact insert with a fixed no. of positions
Number of positions	8
Connection profile	8+PE
Contact numbering	1 - 8
Application	Power
Number of connections per position	1
No. of power contacts	8
No. of control contacts	0
Contact material type	turned
Series	HC-COM

### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### Dimensions

Dimensional drawing	
Width	22.4 mm
Height	38.5 mm
Length	41.6 mm

### Mechanical characteristics

Contact diameter	2.5 mm
------------------	--------

### Connection data

#### Connection technology

Connection technology	Crimp connection
Number of connections per position	1

# HC-COM- 8-EBUC - Contact insert



1408494

<https://www.phoenixcontact.com/us/products/1408494>

Connection in acc. with standard	IEC / EN
----------------------------------	----------

## Conductor connection

Conductor cross section	0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Connection cross section AWG	20 ... 12
Stripping length of the individual wire	7.5 mm

## Electrical properties

Rated voltage (III/3)	500 V
Rated voltage for power contacts	500
Rated surge voltage	6 kV
Rated current	16 A

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

## Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PC

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C (including heating up of contacts)
---------------------------------	--

# HC-COM- 8-EBUC - Contact insert



1408494

<https://www.phoenixcontact.com/us/products/1408494>

## Classifications

### ECLASS

ECLASS-11.0	27440205
ECLASS-12.0	27440205
ECLASS-13.0	27440205

### ETIM

ETIM 9.0	EC000438
----------	----------

### UNSPSC

UNSPSC 21.0	39121500
-------------	----------

# HC-COM- 8-EBUC - Contact insert



1408494

<https://www.phoenixcontact.com/us/products/1408494>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)