

CES-B16-8XSRC-BK - Sealing frame



1411073

<https://www.phoenixcontact.com/us/products/1411073>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sealing frame with screw locking, size: B16, with 8 pre-mounted coned sleeves for a 2 mm ... 11 mm conductor diameter

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1411073 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF67 |
| Product key | BF7CAX |
| Catalog page | Page 677 (C-2-2019) |
| GTIN | 4046356921879 |
| Weight per piece (including packing) | 219.2 g |
| Weight per piece (excluding packing) | 208 g |
| Customs tariff number | 39269097 |
| Country of origin | PL |

CES-B16-8XSRC-BK - Sealing frame

1411073

<https://www.phoenixcontact.com/us/products/1411073>

Technical data


Product properties

| | |
|--------------|----------------------------------|
| Type | B16 |
| Product type | Frame for cable sleeves |
| Frame type | Sealing frame with coned sleeves |

Connection data

| | |
|-------------------|-------------------------------|
| Tightening torque | 2 Nm ... 4 Nm (Locking screw) |
|-------------------|-------------------------------|

Dimensions

| | |
|---------------------------------|--|
| Dimensional drawing |  |
| Width | 58 mm |
| Height | 20 mm |
| Length | 120 mm |
| Drill hole distance, horizontal | 103 mm |
| Drill hole distance, vertical | 32 mm |
| Hole diameter | 5.5 mm |

Installation dimensions

| | |
|-------------------------------|-------|
| Width of the assembly cutout | 35 mm |
| Length of the assembly cutout | 86 mm |

Material specifications

| | |
|----------|-----|
| Material | PA |
| | NBR |

Cable/line

| | |
|-----------------------------|-------------------|
| External cable diameter () | 8x 2 mm ... 11 mm |
|-----------------------------|-------------------|

Characteristics

| | |
|-----------------------|---|
| Number of cable seals | 8 |
|-----------------------|---|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|----------------------------|
| Degree of protection | IP54 |
| | IP65 |
| Ambient temperature (operation) | -40 °C ... 120 °C (static) |

Mounting

CES-B16-8XSRC-BK - Sealing frame



1411073

<https://www.phoenixcontact.com/us/products/1411073>

| | |
|-----------------------|--|
| Assembly instructions | <p>M4 locking screw with 3 mm hex socket head, torque 2 ... 4 Nm</p> <p>The flat gasket supplied should be inserted between the wall and the sealing frame in the case of wall mounting. IP54: for vertical sealing frame mounting/for horizontal sealing frame mounting (downward cable outlet direction). IP65: vertical mounting/horizontal mounting (downward cable outlet direction) of the sealing frame directly on the housing panel and use of a 3.6 mm wide cable binder (e.g., item 3240744).</p> |
|-----------------------|--|

CES-B16-8XSRC-BK - Sealing frame



1411073

<https://www.phoenixcontact.com/us/products/1411073>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 23071590 |
| ECLASS-12.0 | 23071590 |
| ECLASS-13.0 | 23071590 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002498 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31401600 |
|-------------|----------|

CES-B16-8XSRC-BK - Sealing frame



1411073

<https://www.phoenixcontact.com/us/products/1411073>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com