

G-INS-PG48-L68N-NNES-S - Cable gland



1411181

<https://www.phoenixcontact.com/us/products/1411181>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: Brass, nickel-plated, external cable diameter 34 mm ... 44 mm, shielding: no, connecting thread: Pg48, color: silver, with O-ring

Commercial data

Item number	1411181
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF68
Product key	BF7DAX
Catalog page	Page 689 (C-2-2019)
GTIN	4046356923132
Weight per piece (including packing)	375.6 g
Weight per piece (excluding packing)	375.6 g
Customs tariff number	74198090
Country of origin	TR

G-INS-PG48-L68N-NNES-S - Cable gland

1411181

<https://www.phoenixcontact.com/us/products/1411181>

Technical data


Mounting

Assembly instructions	1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
-----------------------	---

Product properties

Product type	Full screw connection
No. of conductors	1
Manufacturer	BIMED
Manufacturer Designation	BSBC-10
Shielded	no

Dimensions

Dimensional drawing	
Length	63 mm
Length of the connecting thread	14 mm
Hole diameter	59.4 mm ... 59.8 mm
Wrench size, union nut	64 mm
Wrench size, support	64 mm
Hexagon angular dimension	70 mm
Thread type connection side	Pg48

Connection data

Tightening torque	50 Nm \pm 2 Nm (Cap nut)
	35 Nm (Support sleeve)

Material specifications

Color	Brass
Material Compression ring	PA 6
Seal material O-ring	Perbunan
Seal material Cable seal	CR
Material for screw connection	Brass, nickel-plated

Cable/line

External cable diameter (Cable 1)	34 mm ... 44 mm
External cable diameter ()	44 mm ... 48 mm (for UL 514 B)
Halogen-free	no

G-INS-PG48-L68N-NNES-S - Cable gland



1411181

<https://www.phoenixcontact.com/us/products/1411181>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (5 bar, 30 min.)
	IP69 (DIN EN 60529 / IEC 60529)
Ambient temperature (operation)	-40 °C ... 100 °C (static)

G-INS-PG48-L68N-NNES-S - Cable gland



1411181

<https://www.phoenixcontact.com/us/products/1411181>

Classifications

ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801

ETIM

ETIM 9.0	EC000441
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

G-INS-PG48-L68N-NNES-S - Cable gland



1411181

<https://www.phoenixcontact.com/us/products/1411181>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com