

# G-INSEC-M40-M68N-NCRS-S - Cable gland



1411192

<https://www.phoenixcontact.com/us/products/1411192>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: Brass, nickel-plated, external cable diameter 19 mm ... 27 mm, shielding: yes, connecting thread: M40 x 1.5, color: silver, with O-ring

## Commercial data

Item number	1411192
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF68
Product key	BF7DBX
Catalog page	Page 690 (C-2-2019)
GTIN	4046356923231
Weight per piece (including packing)	175.96 g
Weight per piece (excluding packing)	172.04 g
Customs tariff number	74198090
Country of origin	DE

# G-INSEC-M40-M68N-NCRS-S - Cable gland



1411192

<https://www.phoenixcontact.com/us/products/1411192>

## Technical data

### Mounting

Assembly instructions	<p><b>Method 1</b> Cut the outer sheath, but do not remove it. Feed the cable through the screw connection and then remove the outer sheath. Now pull the cable back until the connection is established between the cable shield and the contact spring.</p> <p><b>Method 2</b> Push the braided shield back around 15 ... 20 mm over the outer sheath. Insert the cables into the screw connection until the connection is established between the cable shield and the contact spring.</p>
-----------------------	---


### Product properties

Product type	Full screw connection
No. of conductors	1
Manufacturer	Jacob
Manufacturer Designation	50.640 M/EMVD
Shielded	yes
Execution of the strain relief	A

### Characteristics

Category of shock impact	7
Design, Strain relief	A

### Dimensions

Dimensional drawing	
Length	41 mm
Length of the connecting thread	8 mm
Hole diameter	40.1 mm ... 40.3 mm
Wrench size, union nut	43 mm
Wrench size, support	43 mm
Hexagon angular dimension	46 mm
Thread type connection side	M40 x 1.5
Thread pitch	1.5 mm

### Connection data

Tightening torque	13.5 Nm (Union nut: EN 62444)
	13.5 Nm (Support: EN 62444)

# G-INSEC-M40-M68N-NCRS-S - Cable gland



1411192

<https://www.phoenixcontact.com/us/products/1411192>

## Material specifications

Color	Brass
Material Compression ring	PA 6
Seal material O-ring	Perbunan
Seal material Cable seal	CR/NBR
Material for screw connection	Brass, nickel-plated

## Cable/line

External cable diameter (Cable 1)	19 mm ... 27 mm
Halogen-free	no

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP68 (5 bar, 30 minutes)
Ambient temperature (operation)	-40 °C ... 100 °C (static)

# G-INSEC-M40-M68N-NCRS-S - Cable gland



1411192

<https://www.phoenixcontact.com/us/products/1411192>

## Classifications

### ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801

### ETIM

ETIM 9.0	EC000441
----------	----------

### UNSPSC

UNSPSC 21.0	39121300
-------------	----------

# G-INSEC-M40-M68N-NCRS-S - Cable gland



1411192

<https://www.phoenixcontact.com/us/products/1411192>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)