

# G-INSEC-PG9-S68N-NNES-S - Cable gland



1411196

<https://www.phoenixcontact.com/us/products/1411196>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: Brass, nickel-plated, external cable diameter 4 mm ..  
. 8 mm, shielding: yes, connecting thread: Pg9, color: silver, with O-ring

## Commercial data

Item number	1411196
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF68
Product key	BF7DBX
Catalog page	Page 691 (C-2-2019)
GTIN	4046356923279
Weight per piece (including packing)	19.02 g
Weight per piece (excluding packing)	18.84 g
Customs tariff number	74198090
Country of origin	TR

# G-INSEC-PG9-S68N-NNES-S - Cable gland



1411196

<https://www.phoenixcontact.com/us/products/1411196>

## Technical data

### Mounting

Assembly instructions	1) Mount screw connection flange in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
	<b>Method 1</b> Cut the outer sheath, but do not remove it. Feed the cable through the screw connection and then remove the outer sheath. Now pull the cable back until the connection is established between the cable shield and the contact spring.
	<b>Method 2</b> Push the braided shield back around 15 ... 20 mm over the outer sheath. Insert the cables into the screw connection until the connection is established between the cable shield and the contact spring.

### Product properties

Product type	Full screw connection
No. of conductors	1
Manufacturer	BIMED
Manufacturer Designation	BSEM-02
Shielded	yes

### Characteristics

Cable diameter without cable sheath	3 mm (Diameter of braided shield)
-------------------------------------	-----------------------------------

### Dimensions

Dimensional drawing	
Length	29 mm
Length of the connecting thread	6 mm
Hole diameter	15.3 mm ... 15.4 mm
Wrench size, union nut	17 mm
Wrench size, support	17 mm
Hexagon angular dimension	18.9 mm
Thread type connection side	Pg9

### Connection data

Tightening torque	5.5 Nm (Union nut: EN 62444)
	4 Nm (Support: EN 62444)

### Material specifications

# G-INSEC-PG9-S68N-NNES-S - Cable gland



1411196

<https://www.phoenixcontact.com/us/products/1411196>

Color	Brass
Material Compression ring	PA 6
Seal material O-ring	Perbunan
Seal material Cable seal	CR
Material for screw connection	Brass, nickel-plated

## Cable/line

External cable diameter (Cable 1)	4 mm ... 8 mm
Halogen-free	no

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 100 °C (static)

# G-INSEC-PG9-S68N-NNES-S - Cable gland



1411196

<https://www.phoenixcontact.com/us/products/1411196>

## Classifications

### ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140801

### ETIM

ETIM 9.0	EC000441
----------	----------

### UNSPSC

UNSPSC 21.0	39121300
-------------	----------

# G-INSEC-PG9-S68N-NNES-S - Cable gland



1411196

<https://www.phoenixcontact.com/us/products/1411196>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)