

1411487

https://www.phoenixcontact.com/us/products/1411487

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



EVO connector set, B6 series, metal housing, consisting of: sleeve housing 1411448, panel mounting base 1411319, EVO screw connection 1411439, pin contact insert 1407728, socket contact insert 1407727

### Commercial data

Item number	1411487
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF63
Product key	BF7AFX
Catalog page	Page 637 (C-2-2017)
GTIN	4046356932875
Weight per piece (including packing)	450 g
Weight per piece (excluding packing)	448.62 g
Customs tariff number	85366990
Country of origin	CN



1411487

https://www.phoenixcontact.com/us/products/1411487

### Set consists of

### HC-B06-I-PT-F - Contact insert

1407727

https://www.phoenixcontact.com/us/products/1407727



Contact insert, number of positions: 6+PE, size: B6, number of connections per position: 1, Socket, Push-in connection, 500 V, 16 A, 0.14  $\rm mm^2 \dots 2.5~mm^2$ , application: Power

### HC-B06-I-PT-M - Contact insert

1407728

https://www.phoenixcontact.com/us/products/1407728



Contact insert, number of positions: 6+PE, size: B6, number of connections per position: 1, Pin, Push-in connection, 500 V, 16 A, 0.14  $\rm mm^2 \dots 2.5~mm^2$ , application: Power



1411487

https://www.phoenixcontact.com/us/products/1411487

### HC-EVO-B06-HLFS-EL-AL - Housing

1411448

https://www.phoenixcontact.com/us/products/1411448



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B6, for single locking latch, height: 64 mm, without EVO screw connection.

#### HC-STA-B06-BWSC-ELC-AL - Housing

1411319

https://www.phoenixcontact.com/us/products/1411319



Panel mounting base B6, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, height: 30.5 mm, cable gland: none, protective cover: yes, Standard, with flat gasket



1411487

https://www.phoenixcontact.com/us/products/1411487

HC-B-G-M20-EC-AL - Cable gland

1411439

https://www.phoenixcontact.com/us/products/1411439



EVO EMC cable gland with bayonet locking, B series, size M20, cable diameter: 9  $\dots$  13 mm



1411487

https://www.phoenixcontact.com/us/products/1411487

### Technical data

### Product properties

Туре	B6		
Product type	Connector set		
Number of positions	6		
Connection profile	6+PE		
No. of cable outlets	1		
Housing type	Complete housing		
Seal present	yes		
Protective cover	yes		
Series	НС-В		
Cable outlet	straight		
insulation characteristics			
Overvoltage category	III		
Degree of pollution	3		

### Electrical properties

Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A

### Connection data

Connection method	Push-in connection
Connection technology	Push-in connection
Conductor cross section	0.14 mm <sup>2</sup> 2.5 mm <sup>2</sup> (with ferrule)
	0.14 mm <sup>2</sup> 2.5 mm <sup>2</sup> (with ferrule)
Connection cross section AWG	26 14
Tightening torque	0.5 Nm 1.7 Nm (Fixing screws for panel mounting base)
Stripping length	8 mm 10 mm

### Dimensions

Dimensional drawing	70 52 \$2 \$2 \$3 \$4 \$4
Width	53 mm
Height	94.5 mm
Length	80.5 mm
Drill hole distance, horizontal	70 mm
Drill hole distance, vertical	32 mm



1411487

https://www.phoenixcontact.com/us/products/1411487

#### Installation dimensions

Width of the assembly cutout	35 mm
Length of the assembly cutout	52 mm

### Material specifications

Material Housing	Die-cast aluminum, corrosion-resistant
Material Protective cover	PA
Flammability rating according to UL 94	V0
Seal material Profile gasket	NBR
Seal material Flat gasket	NBR
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA
Locking latch material	PA
Impact strength	IK08

### Cable/line

External cable diameter ()	9 mm 12 mm

### Mechanical properties

#### Mechanical data

Locking type	Latch
Insertion/withdrawal cycles	≥ 500

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66 (with locked protective cover)
	IP67 (when plugged in)
	IP66
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C 100 °C

### Mounting

Mounting type	Screw mounting
Assembly instructions	Coding also using the CP-HC (1686478) coding profiles. HC-B6 / HC-B10for two coding profiles. HC-B16/ HC-B24for four coding profiles.
	Connectors may only be operated when there is no load/the power is switched off. Can be used for solid wires and stranded wires with ferrule.



1411487

https://www.phoenixcontact.com/us/products/1411487

## Classifications

### **ECLASS**

	ECLASS-11.0	27440101			
	ECLASS-12.0	27440113			
	ECLASS-13.0	27440113			
ΕΊ	ETIM				
	ETIM 9.0	EC002636			
U	UNSPSC				
	UNSPSC 21.0	39121400			



1411487

https://www.phoenixcontact.com/us/products/1411487

## Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com