# HC-HPR-B06-HHWH-1STM20-EM-BK - Housing



https://www.phoenixcontact.com/us/products/1411878

**PHŒNIX** CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON B6 sleeve housing, HPR series, with screw locking, with M20 thread, lateral outlet, for increased environmental and EMC requirements

### Your advantages

• Vibration and shock: IEC 61373/EN 50155, category 1, class 1B

### Commercial data

Item number	1411878
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF60
Product key	BF7AAI
Catalog page	Page 626 (C-4-2015)
GTIN	4046356944250
Weight per piece (including packing)	497.2 g
Weight per piece (excluding packing)	497.2 g
Customs tariff number	85389099
Country of origin	CN

# HC-HPR-B06-HHWH-1STM20-EM-BK - Housing

1411878

https://www.phoenixcontact.com/us/products/1411878



### Technical data

### Notes

General	For contact inserts HC-B6, BB10, DD24, M Tall housings for extra large wiring space
Product properties	
Туре	B6

Product type	Housing with screw locking
Product family	HC-HPR-B
Application	Railway applications
No. of cable outlets	1
Type of the screw connection	1x M20
Housing type	Sleeve housing
Protective cover	no
Series	HPR-B6
Cable outlet	lateral
Pg screw connection	none

### Dimensions

Dimensional drawing	
Width	58 mm
Height	100.5 mm
Length	132 mm

### Material specifications

Housing surface material	Powder-coated, black
Locking latch material	Stainless steel
Impact strength	IK09
Housing material	die-cast aluminum

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66
	IP68 (0.5 bar / 24 h)
	IP69 (ISO 20653:2013-02)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C

# HC-HPR-B06-HHWH-1STM20-EM-BK - Housing

#### 1411878

https://www.phoenixcontact.com/us/products/1411878



### Mechanical properties

#### Mechanical data

Type of the screw connection	1x M20
Locking type	Screw

### Mounting

Assembly instructions	M6 locking screw, slotted hexagon head screw (SW10),
	tightening torque: 4 Nm

1411878

https://www.phoenixcontact.com/us/products/1411878



## Classifications

### ECLASS

ECLASS-12.0 27440202	ECLASS-11.0	27440202
	ECLASS-12.0	27440202
ECLASS-13.0 27440202	ECLASS-13.0	27440202

### ETIM

	ETIM 9.0	EC000437	
UN	UNSPSC		
	UNSPSC 21.0	31261500	



1411878

https://www.phoenixcontact.com/us/products/1411878

# 

### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com