

# CUC-V06-C1PBK-S/R4CE8:1 - RJ45 connector



1414408

<https://www.phoenixcontact.com/us/products/1414408>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 connector, design: RJ45, degree of protection: IP67, number of positions: 8, 1 Gbps, CAT6, material: Plastic, connection method: Crimp connection, connection cross section: AWG 24- 27, cable outlet: straight, color: black, Ethernet/PROFINET

## Commercial data

Item number	1414408
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB17
Product key	ABNNAB
Catalog page	Page 350 (C-2-2019)
GTIN	4055626028309
Weight per piece (including packing)	19.8 g
Weight per piece (excluding packing)	19.8 g
Customs tariff number	85366990
Country of origin	DE

# CUC-V06-C1PBK-S/R4CE8:1 - RJ45 connector



1414408

<https://www.phoenixcontact.com/us/products/1414408>

## Technical data

### Product properties

Type	RJ45
Product type	Data connector (cable side)
Sensor type	Ethernet/PROFINET
Number of positions	8
Connection profile	RJ45
No. of cable outlets	1
Type	RJ45
Shielded	yes
Cable outlet	straight

### Insulation characteristics

Overvoltage category	I
Degree of pollution	2

### Electrical properties

Rated voltage (III/3)	72 V (DC)
Rated current	1 A
Frequency range	to 250 MHz
Nominal voltage $U_N$	72 V (DC)
Nominal current $I_N$	1.75 A
Transmission medium	Copper
Transmission characteristics (category)	CAT6
Transmission speed	1 Gbps

### Connection data

#### Connection technology

Connection method	Crimp connection
Connection cross section AWG	24 ... 27 (flexible)
Conductor cross section	0.1 mm <sup>2</sup> ... 0.2 mm <sup>2</sup> (flexible)

### Dimensions

Width	38.4 mm
Height	53 mm
Length	19.9 mm

### Material specifications

Color	black
Flammability rating according to UL 94	V0
Seal material, O-ring	NBR
Seal material	TPE
Cable seal material	NBR

# CUC-V06-C1PBK-S/R4CE8:1 - RJ45 connector



1414408

<https://www.phoenixcontact.com/us/products/1414408>

Contact material	Phosphor bronze
Contact surface material	Gold
Contact carrier material	PC
O-ring material	FPM
Housing material	Plastic

## Cable/line

External cable diameter ( )	5 mm ... 8.5 mm
Cable cross section	0.1 mm <sup>2</sup>

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	≥ 750
-----------------------------	-------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 °C ... 60 °C

# CUC-V06-C1PBK-S/R4CE8:1 - RJ45 connector



1414408

<https://www.phoenixcontact.com/us/products/1414408>

## Classifications

### ECLASS

ECLASS-11.0	27440101
ECLASS-12.0	27440113
ECLASS-13.0	27440116

### ETIM

ETIM 9.0	EC002636
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# CUC-V06-C1PBK-S/R4CE8:1 - RJ45 connector



1414408

<https://www.phoenixcontact.com/us/products/1414408>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)