

FO connecting cable - FOC-HCS-GI-1005/M12-C/M12-C/5 - 1416693

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled FO cable, round cable, 200/230 µm PCF-GI fiber, M12 to M12, for installation inside buildings, length: 5 m

PCF-GI cable, assembled with M12 connectors to M12

Product Description


PCF-GI cable, assembled with M12 connector to M12

Your advantages

- ✓ 2.2 mm individual wires made from polyvinyl chloride (PVC)
- ✓ Assembled patch cable with test report
- ✓ M12-OPTIC with recessed ferrules to protect against damage
- ✓ optimized polishing for even better attenuation values
- ✓ Rugged installation cable for indoor use
- ✓ Gradient index fiber for maximum performance requirements in terms of transmission bandwidth
- ✓ Rugged polyurethane (PUR) outer sheath
- ✓ Highly tear-resistant aramid strain relief elements
- ✓ Pin connector pattern in accordance with DIN/IEC 61754-27
- ✓ Included in PROFINET planning guideline (v1.14)
- ✓ Robust connector, IP65/IP67
- ✓ Can be used in 10/100/1000 Mbps Ethernet systems
- ✓ Halogen-free, ozone, and UV resistant



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 480789
GTIN	4046356480789

FO connecting cable - FOC-HCS-GI-1005/M12-C/M12-C/5 - 1416693

Weight per Piece (excluding packing)	380.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Mechanical characteristics

Connection method	M12 circular connector
Weight	388.1 g
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (operation)	-20 °C ... 70 °C
	-20 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65
	IP67

Standards and Regulations


Duty cycle testing	suitable for drag chain
Resistance to UV radiation	yes
Impact strength	2 Nm / 10 x
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	27061003
---------------	----------

FO connecting cable - FOC-HCS-GI-1005/M12-C/M12-C/5 - 1416693

Classifications

eCl@ss

eCl@ss 11.0	27061003
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27061000
eCl@ss 6.0	27061000
eCl@ss 7.0	27061090
eCl@ss 9.0	27061003

ETIM

ETIM 3.0	EC000034
ETIM 4.0	EC000034
ETIM 6.0	EC001263
ETIM 7.0	EC001263

UNSPSC

UNSPSC 6.01	30211832
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	26121607
UNSPSC 18.0	26121607
UNSPSC 19.0	26121607
UNSPSC 20.0	26121607
UNSPSC 21.0	26121607