

SACC-4P-DSI-M12FSD/FSD-M16 - Device connector rear mounting



1424326

<https://www.phoenixcontact.com/us/products/1424326>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 4-position, Socket, straight, M12, coding: D, on Socket straight M12, D, Bipolar mounting, M16 x 1.5

Commercial data

Item number	1424326
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB28
Product key	ABQFAA
Catalog page	Page 53 (C-2-2019)
GTIN	4046356730525
Weight per piece (including packing)	43.8 g
Weight per piece (excluding packing)	32.5 g
Customs tariff number	85366990
Country of origin	DE

SACC-4P-DSI-M12FSD/FSD-M16 - Device connector rear mounting



1424326

<https://www.phoenixcontact.com/us/products/1424326>

Technical data

Notes

General	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Safety note	<p data-bbox="849 819 1452 902">WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul data-bbox="849 916 1469 2087" style="list-style-type: none"><li data-bbox="849 916 1430 1025">• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.<li data-bbox="849 1041 1469 1234">• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.<li data-bbox="849 1249 1437 1305">• The products are suitable for applications in plant, controller, and electrical device engineering.<li data-bbox="849 1321 1449 1377">• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.<li data-bbox="849 1393 1425 1449">• Assembled products may not be manipulated or improperly opened.<li data-bbox="849 1464 1449 1543">• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).<li data-bbox="849 1559 1430 1615">• When using the product in direct connection with third-party manufacturers, the user is responsible.<li data-bbox="849 1630 1398 1686">• For operating voltages > 50 V AC, conductive connector housings must be grounded<li data-bbox="849 1702 1409 1780">• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.<li data-bbox="849 1796 1417 1960">• Observe the corresponding technical data. You will find information:<ul data-bbox="849 1848 1417 1960" style="list-style-type: none"><li data-bbox="849 1848 1011 1877">o On the product<li data-bbox="849 1877 1062 1906">o On the packing label<li data-bbox="849 1906 1153 1935">o In the supplied documentation<li data-bbox="849 1935 1417 1960">o Online at phoenixcontact.com/products under the product<li data-bbox="849 1975 1337 2004">• Only use tools recommended by Phoenix Contact<li data-bbox="849 2020 1449 2087">• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products

SACC-4P-DSI-M12FSD/FSD-M16 - Device connector rear mounting



1424326

<https://www.phoenixcontact.com/us/products/1424326>

	<ul style="list-style-type: none">• Ensure that the protective or functional ground has been properly connected.• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
--	---

Mounting

Mounting type	Bipolar mounting M16 x 1.5
---------------	----------------------------

Product properties

Product type	Circular connectors (device side)
Number of positions	4
Coding	D
Thread type	M12

Insulation characteristics

Overvoltage category	II
Degree of pollution	2

Material specifications

Flammability rating according to UL 94	HB
Seal material	FKM
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Brass, nickel-plated

Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U_N	60 V
Nominal current I_N	4 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

Connector

Connection 1

Head design	Socket
-------------	--------

SACC-4P-DSI-M12FSD/FSD-M16 - Device connector rear mounting



1424326

<https://www.phoenixcontact.com/us/products/1424326>

Head cable outlet	straight
Head thread type	M12
Coding	D

Connection 2

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	D

Cable/line

Ambient temperature (operation)	-40 °C ... 85 °C (cable, fixed installation)
	-25 °C ... 85 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP65/IP67
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)
	-40 °C ... 85 °C (without mechanical actuation)
	-25 °C ... 85 °C (Cable, flexible installation)
	-40 °C ... 85 °C (cable, fixed installation)

Standards and regulations

M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SACC-4P-DSI-M12FSD/FSD-M16 - Device connector rear mounting



1424326

<https://www.phoenixcontact.com/us/products/1424326>

Classifications

ECLASS

ECLASS-11.0	27440392
ECLASS-12.0	27440392
ECLASS-13.0	27440392

ETIM

ETIM 9.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-4P-DSI-M12FSD/FSD-M16 - Device connector rear mounting



1424326

<https://www.phoenixcontact.com/us/products/1424326>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com