

# SAC-6P-MS/ 2,0-970 SCO - Bus system cable



1428490

<https://www.phoenixcontact.com/us/products/1428490>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, VARAN (100 Mbps), 6-position, SANTOPRENE halogen-free/TPE halogen-free, black RAL 9005, shielded (Tinned copper-braided shield, approx. 85% covering), Plug straight M12 SPEEDCON, coding: A, on free cable end, cable length: 2 m

## Commercial data

Item number	1428490
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF04
Product key	BF1CMM
Catalog page	Page 324 (PC-2011)
GTIN	4046356322775
Weight per piece (including packing)	180 g
Weight per piece (excluding packing)	178.3 g
Customs tariff number	85444290
Country of origin	PL

# SAC-6P-MS/ 2,0-970 SCO - Bus system cable



1428490

<https://www.phoenixcontact.com/us/products/1428490>

## Technical data

### Product properties

Product type	Data cable preassembled
Sensor type	VARAN
Number of positions	6
Application	Standard
No. of cable outlets	1
Coding	A

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Interfaces

Bus system	VARAN
Signal type/category	VARAN, 100 Mbps

### Signaling

Status display	No
Status display present	No

### Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	30 V AC
	30 V DC
Nominal current $I_N$	2 A
Transmission medium	Copper

### Material specifications

Flammability rating according to UL 94	HB
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

### Connection data

#### Pin assignment

Contact   Color (signal designation)   Contact (optional)	1 (Plug)
	4 (Plug)
	6 (Plug)   BU (Power)
	7 (Plug)   BN (Power)
	5 (Plug)   GNWH (RD+)

# SAC-6P-MS/ 2,0-970 SCO - Bus system cable



1428490

<https://www.phoenixcontact.com/us/products/1428490>

	8 (Plug)   GN (RD-)
	2 (Plug)   OGWH (TD+)
	3 (Plug)   OG (TD-)

## Connector

### Connection 1

Type	Plug straight M12 SPEEDCON
Number of positions	6
Locking type	SPEEDCON
Coding type	A (Standard)


### Connection 2

Type	free cable end
------	----------------

## Cable/line

Cable length	2 m
--------------	-----

### VARAN [970]

Dimensional drawing	
Cable weight	81 kg/km
Number of positions	6
Shielded	yes
Cable type	VARAN [970]
Conductor structure	1x2xAWG22/19 + 1x4xAWG24/19
Conductor structure signal line	19x 0.13 mm
AWG signal line	24
Conductor cross section	4x 0.25 mm <sup>2</sup> (Signal line) 2x 0.38 mm <sup>2</sup> (Power supply)
Wire diameter incl. insulation	1.35 mm (Signal line) 1.5 mm (Power supply)
External cable diameter	7.80 mm ±0.2 mm
Outer sheath, material	SANTOPRENE halogen-free
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material, filler	Yarn
Material wire insulation	PP
Single wire, color	brown, blue, white/orange, white/green, green, orange

# SAC-6P-MS/ 2,0-970 SCO - Bus system cable



1428490

<https://www.phoenixcontact.com/us/products/1428490>

Type of pair shielding	Tinned copper braided shield, 95 % covering
Overall twist	1 star quad and 2 wires with 2 fillers
Max. conductor resistance	77 $\Omega$ /m (Data cable)
Insulation resistance	5 G $\Omega$ *km (Data cable)
Wave impedance	100 $\Omega$ $\pm$ 15 %
Working capacitance	50 nF (Data cable)
Nominal voltage, cable	125 V (Data cable)
	48 V (Power supply)
Test voltage	2000 V (Power supply)
	max. 700 V AC (Data cable)
Smallest bending radius, fixed installation	$\geq$ 93 mm
Smallest bending radius, movable installation	$\geq$ 93 mm
Max. bending cycles	3000000
Halogen-free	in accordance with DIN EN 50267-2-1
Ambient temperature (operation)	-20 °C ... 80 °C (Cable)
Ambient temperature (installation)	0 °C ... 50 °C

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

# SAC-6P-MS/ 2,0-970 SCO - Bus system cable



1428490

<https://www.phoenixcontact.com/us/products/1428490>

## Classifications

### ECLASS

ECLASS-11.0	27060307
ECLASS-12.0	27060307
ECLASS-13.0	27060307

### ETIM

ETIM 9.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SAC-6P-MS/ 2,0-970 SCO - Bus system cable



1428490

<https://www.phoenixcontact.com/us/products/1428490>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)