

https://www.phoenixcontact.com/us/products/1430488



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M12 metal sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field

#### Your advantages

- Reliable protection of unoccupied slots during transport and use in the field
- Robust and reliable: brass protective cap up to IP69K degree of protection
- · Protected against splash water and dust by the internal seal
- · Easy assembly by hand or using a wrench

#### Commercial data

| Item number                          | 1430488            |
|--------------------------------------|--------------------|
| Packing unit                         | 10 pc              |
| Minimum order quantity               | 10 pc              |
| Sales key                            | AB26               |
| Product key                          | ABQEQA             |
| Catalog page                         | Page 54 (C-2-2019) |
| GTIN                                 | 4046356325776      |
| Weight per piece (including packing) | 9.64 g             |
| Weight per piece (excluding packing) | 9.5 g              |
| Customs tariff number                | 74198090           |
| Country of origin                    | DE                 |



https://www.phoenixcontact.com/us/products/1430488



### Technical data

#### Notes

| General                                | Use up to max. 48 V AC and 60 V DC |  |
|--|------------------------------------|--|
| Product properties                     |                                    |  |
| Product type                           | Protective cap                     |  |
| Thread type                            | M12                                |  |
| Environmental and real-life conditions |                                    |  |

#### Ε

#### Ambient conditions

| Ambient temperature (operation) | -40 °C 85 °C |
|---------------------------------|--------------|
|---------------------------------|--------------|



1430488

https://www.phoenixcontact.com/us/products/1430488

## Classifications

UNSPSC 21.0

#### **ECLASS**

| ECLASS-11.0 | 23111190 |
|-------------|----------|
| ECLASS-12.0 | 23111190 |
| ECLASS-13.0 | 23111190 |
| ETIM        |          |
| ETIM 9.0    | EC000032 |
| UNSPSC      |          |

31261500



https://www.phoenixcontact.com/us/products/1430488



### Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com