

# SACC-DSI-M12FS-8CON-L180P - Device connector rear mounting



1436343

<https://www.phoenixcontact.com/us/products/1436343>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator flush-type connector, socket, 8-pos., M12, A-coded, rear/screw mounting with Pg9 thread, with straight solder connection, plastic version

## Commercial data

Item number	1436343
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB23
Product key	ABQELL
Catalog page	Page 263 (C-2-2013)
GTIN	4046356438315
Weight per piece (including packing)	7.21 g
Weight per piece (excluding packing)	7.21 g
Customs tariff number	85366990
Country of origin	DE

# SACC-DSI-M12FS-8CON-L180P - Device connector rear mounting



1436343

<https://www.phoenixcontact.com/us/products/1436343>

## Technical data

### Notes

General	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
---------	--

### Mounting

Mounting type	Rear mounting Pg9 With locking nut
Assembly instructions	With locking nut

### Product properties

Product type	Circular connectors (device side)
Number of positions	8
Shielded	no
Coding	A
Thread type	M12

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Material specifications

Color	black
Flammability rating according to UL 94	HB
Seal material	Viton
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	PA 6.6

### Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	30 V
Nominal current $I_N$	2 A
Max. conductor resistance	57.6 m $\Omega$ /m

### Connection data

Conductor connection

# SACC-DSI-M12FS-8CON-L180P - Device connector rear mounting



1436343

<https://www.phoenixcontact.com/us/products/1436343>

Connection method	Wave soldering
Contact connection type	Socket
Conductor cross section	0.25 mm <sup>2</sup>
Tightening torque	1.25 Nm ... 1.5 Nm (Installation-side)

## Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

## Connector

### Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Coding	A

## Cable/line

Wire diameter incl. insulation	1.15 mm ±0.07 mm
Cable cross section	0.25 mm <sup>2</sup>
Conductor structure signal line	14x 0.15 mm
Thickness, insulation	0.21 mm
Nominal voltage, cable	300 V
Test voltage, cable	2000 V AC
Cable resistance	≤ 57.6 mΩ/m
Cable insulation resistance	≥ 20 MΩ*km
Ambient temperature (operation)	-40 °C ... 85 °C (cable, fixed installation) -25 °C ... 85 °C (Cable, flexible installation)

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67 IP67
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket) -40 °C ... 85 °C (without mechanical actuation) -25 °C ... 85 °C (Cable, flexible installation) -40 °C ... 85 °C (cable, fixed installation)

## Standards and regulations

### M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

# SACC-DSI-M12FS-8CON-L180P - Device connector rear mounting



1436343

<https://www.phoenixcontact.com/us/products/1436343>

## Classifications

### ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

### ETIM

ETIM 9.0	EC002635
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# SACC-DSI-M12FS-8CON-L180P - Device connector rear mounting



1436343

<https://www.phoenixcontact.com/us/products/1436343>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)