

1436398

https://www.phoenixcontact.com/us/products/1436398

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator flush-type connector, male, 5-pos., M12, A-coded, front/screw mounting with M16 thread, with solder cups, plastic version

## Your advantages

• Standard pin assignments and codings for signal transmission with a uniform design-in design

### Commercial data

Item number	1436398
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB23
Product key	ABQEEJ
Catalog page	Page 241 (C-2-2013)
GTIN	4046356438346
Weight per piece (including packing)	6.745 g
Weight per piece (excluding packing)	5.7 g
Customs tariff number	85366990
Country of origin	DE



1436398

https://www.phoenixcontact.com/us/products/1436398

#### Technical data

#### **Notes**

The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

#### Safety note

#### Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only.
   The products must be regularly inspected for damage.
   Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
- The products are suitable for applications in plant, controller, and electrical device engineering.
- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
- Observe the corresponding technical data. You will find information:
- o On the product
- o On the packing label
- o In the supplied documentation
- o Online at phoenixcontact.com/products under the product
- · Only use tools recommended by Phoenix Contact
- Use a protective cap to protect connectors that are not in use.
   The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products



1436398

https://www.phoenixcontact.com/us/products/1436398

Contact connection type

	<ul> <li>Ensure that the protective or functional ground has been properly connected.</li> </ul>
	<ul> <li>VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector</li> </ul>
	<ul> <li>The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).</li> </ul>
Mounting	
Mounting type	Front mounting M16 x 1.5 With flat nut
Assembly instructions	With flat nut
Product properties	
• •	Circular connectors (device side)
Product type  Number of positions	Circular connectors (device side) 5
No. of cable outlets	1
Coding	A
Thread type	M12
Till cad type	10112
Insulation characteristics	
Overvoltage category	II
Degree of pollution	3
Material specifications	
Color	black
Flammability rating according to UL 94	НВ
Seal material	Viton
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	PA 6.6
Electrical properties	
Rated surge voltage	1.5 kV
Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U <sub>N</sub>	60 V
Nominal current I <sub>N</sub>	4 A
Connection data	
Conductor connection  Connection method	Solder cup
Connection metrica	Oolder cup

Pin



1436398

https://www.phoenixcontact.com/us/products/1436398

Conductor cross section flexible	0.25 mm²
Tightening torque	1.25 Nm 1.5 Nm (Installation-side)

## Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	> 100	

### Connector

#### Connection 1

Head design	Pin
Head cable outlet	straight
Head thread type	M12
Coding	A

### Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
	-40 °C 85 °C (without mechanical actuation)

## Standards and regulations

#### M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101



1436398

https://www.phoenixcontact.com/us/products/1436398

## Classifications

### **ECLASS**

	ECLASS-11.0	27440102
	ECLASS-12.0	27440116
	ECLASS-13.0	27440116
ETIM		
ETIM		
	ETIM 9.0	EC002635
UNSPSC		
	UNSPSC 21.0	39121400



1436398

https://www.phoenixcontact.com/us/products/1436398

## Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com