

SACC-M12 NUT PRESS - Housing screw connection



1437889

<https://www.phoenixcontact.com/us/products/1437889>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Housing screw connection, Socket, M12, Front mounting, THR solder connection, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1237410

Your advantages

- Easy device integration, thanks to mechanical port screw connections with press-in contour
- Flexible PCB assembly: two-piece connectors for wave and THR soldering

Commercial data

Item number	1437889
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB23
Product key	ABQACK
Catalog page	Page 259 (C-2-2013)
GTIN	4046356457552
Weight per piece (including packing)	10.28 g
Weight per piece (excluding packing)	10.26 g
Customs tariff number	74198090
Country of origin	DE

SACC-M12 NUT PRESS - Housing screw connection



1437889

<https://www.phoenixcontact.com/us/products/1437889>

Technical data

Notes

General	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
---------	--

Product properties

Product type	Panel mounting base
Thread type	M12

Connection data

Connection method	THR solder connection
-------------------	-----------------------

Material specifications

Material	CuZn (nickel-plated)
Seal material	EPDM

Connector

Connection 1

Head design	Socket
Head thread type	M12

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked) IP67, when in locked state
Ambient temperature (operation)	-25 °C ... 105 °C (Plug / socket) -40 °C ... 105 °C (without mechanical actuation)

Standards and regulations

M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

Mounting

SACC-M12 NUT PRESS - Housing screw connection



1437889

<https://www.phoenixcontact.com/us/products/1437889>

Mounting type	Front mounting Press-in mounting
Assembly instructions	Press-in mounting

SACC-M12 NUT PRESS - Housing screw connection



1437889

<https://www.phoenixcontact.com/us/products/1437889>

Classifications

ECLASS

ECLASS-11.0	27440224
ECLASS-12.0	27440224
ECLASS-13.0	27440224

ETIM

ETIM 9.0	EC003556
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-M12 NUT PRESS - Housing screw connection



1437889

<https://www.phoenixcontact.com/us/products/1437889>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com