

SACC-DSIV-M 8MS-4CON-L 90 - Device connector rear mounting



1440096

<https://www.phoenixcontact.com/us/products/1440096>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 4-position, Pin, angled, M8, coding: A, Rear mounting, M8 x 1, Wave soldering

Your advantages

- Standard pin assignments and codings for signal transmission with a uniform design-in design

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1440096 |
| Packing unit | 20 pc |
| Minimum order quantity | 20 pc |
| Sales key | AB22 |
| Product key | ABQJAA |
| Catalog page | Page 230 (C-2-2013) |
| GTIN | 4046356480888 |
| Weight per piece (including packing) | 4.63 g |
| Weight per piece (excluding packing) | 4.5 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

SACC-DSIV-M 8MS-4CON-L 90 - Device connector rear mounting



1440096

<https://www.phoenixcontact.com/us/products/1440096>

Technical data

Mounting

| | |
|-----------------------|------------------------------------|
| Mounting type | Rear mounting M8 x 1 With flat nut |
| Assembly instructions | With flat nut |

Product properties

| | |
|---------------------|-----------------------------------|
| Product type | Circular connectors (device side) |
| Number of positions | 4 |
| Shielded | no |
| Coding | A |
| Thread type | M8 |

Insulation characteristics

| | |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution | 3 |

Material specifications

| | |
|--|----------------------|
| Flammability rating according to UL 94 | HB |
| Seal material | NBR |
| Contact material | Cu alloy |
| Contact surface material | Au |
| Contact carrier material | PA 6.6 |
| Material for screw connection | Brass, nickel-plated |

Electrical properties

| | |
|-----------------------|----------------------------|
| Rated surge voltage | 1.5 kV |
| Contact resistance | $\leq 3 \text{ m}\Omega$ |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage U_N | 48 V AC 60 V DC |
| Nominal current I_N | 4 A |

Connection data

Conductor connection

| | |
|-------------------------|----------------|
| Connection method | Wave soldering |
| Contact connection type | Pin |

Connector

Connection 1

| | |
|-------------------|--------|
| Head design | Pin |
| Head cable outlet | angled |

SACC-DSIV-M 8MS-4CON-L 90 - Device connector rear mounting



1440096

<https://www.phoenixcontact.com/us/products/1440096>

| | |
|------------------|----|
| Head thread type | M8 |
| Coding | A |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Degree of protection | IP67 |
| | IP67 |
| Ambient temperature (operation) | -25 °C ... 85 °C |
| | -25 °C ... 85 °C |

Standards and regulations

| | |
|--------------------------|-----------------|
| Standard designation | M8 connector |
| Standards/specifications | IEC 61076-2-104 |

SACC-DSIV-M 8MS-4CON-L 90 - Device connector rear mounting



1440096

<https://www.phoenixcontact.com/us/products/1440096>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

SACC-DSIV-M 8MS-4CON-L 90 - Device connector rear mounting



1440096

<https://www.phoenixcontact.com/us/products/1440096>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com