

SAC- 1,5/0,1-116/2XBI-1L-Z - Double valve connector cable



1458347

<https://www.phoenixcontact.com/us/products/1458347>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Double valve connector cable, 4-position, PUR/PVC, black, free cable end, on Valve connector BI (11 mm), with 1 LED, Wiring: Z diode and Valve connector BI (11 mm), with 1 LED, Wiring: Z diode, cable length: 1.5 m, valve connector spacing: 0.1 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Efficient: control valves with two connections via a single connecting cable
- Convenient: increased machine availability thanks to quick and easy diagnostics

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1458347 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF07 |
| Product key | BF1DIA |
| Catalog page | Page 243 (C-2-2019) |
| GTIN | 4046356638784 |
| Weight per piece (including packing) | 148.8 g |
| Weight per piece (excluding packing) | 148.8 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

SAC- 1,5/0,1-116/2XBI-1L-Z - Double valve connector cable



1458347

<https://www.phoenixcontact.com/us/products/1458347>

Technical data

Product properties

| | |
|----------------------|--|
| Product type | Sensor/actuator cable with valve connector |
| Number of positions | 4 |
| Application | Standard |
| No. of cable outlets | 1 |
| Shielded | no |

Insulation characteristics

| | |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution | 3 |

Material specifications

| | |
|--|--------|
| Flammability rating according to UL 94 | HB |
| Seal material | TPU |
| Material housing valve plug | TPU |
| Contact material | CuSn |
| Valve plug contact insert material | PA 6.6 |
| Contact surface material | Sn |

Electrical properties

| | |
|-----------------------|----------|
| Insulation resistance | ≥ 100 MΩ |
| Nominal voltage U_N | 24 V AC |
| | 24 V DC |
| Nominal current I_N | 4 A |
| Protective circuit | Z diode |

Valve connector characteristics

| | |
|------------------|------------------------------------|
| Fixing screws | M3 x 29 |
| Pulse power | 40 W (at 100 μs square-wave pulse) |
| Terminal voltage | 70 V (at 2 mA constant current) |
| Reverse voltage | 50 V |

Mechanical properties

Mechanical data

| | |
|-----------------------------|----|
| Insertion/withdrawal cycles | 50 |
|-----------------------------|----|

Signaling

| | |
|------------------------|-------|
| Status display | 1 LED |
| Status display present | Yes |

Connector

Connection 1

SAC- 1,5/0,1-116/2XBI-1L-Z - Double valve connector cable



1458347

<https://www.phoenixcontact.com/us/products/1458347>

| | |
|------|----------------|
| Type | free cable end |
|------|----------------|

Connection 2

| | |
|----------|----------------------------|
| Type | Valve connector BI (11 mm) |
| Material | CuSn (Contact) |
| | Sn (Contact surface) |
| | PA 6.6 (Contact carriers) |
| | TPU (Housing) |


Connection 3

| | |
|----------|----------------------------|
| Type | Valve connector BI (11 mm) |
| Material | CuSn (Contact) |
| | Sn (Contact surface) |
| | PA 6.6 (Contact carriers) |
| | TPU (Housing) |

Cable/line

| | |
|--------------|-------|
| Cable length | 1.5 m |
| | 0.1 m |

PUR/PVC, 0.75 mm², black [116]

| | |
|---------------------------------|--|
| Dimensional drawing |  |
| Cable weight | 57 kg/km |
| UL AWM Style | 20549 |
| Number of positions | 4 |
| Shielded | no |
| Cable type | PUR/PVC, 0.75 mm ² , black [116] |
| Conductor structure signal line | 24x 0.20 mm |
| AWG signal line | 18 |
| Conductor cross section | 4x 0.75 mm ² |
| Wire diameter incl. insulation | 1.7 mm ±0.05 mm |
| External cable diameter | 6.30 mm ±0.2 mm |
| Outer sheath, material | PUR |
| External sheath, color | black |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PVC |
| Single wire, color | black 1, black 2, black 3, green/yellow |
| Overall twist | 4 wires, twisted |

SAC- 1,5/0,1-116/2XBI-1L-Z - Double valve connector cable



1458347

<https://www.phoenixcontact.com/us/products/1458347>

| | |
|---|--|
| Max. conductor resistance | 26 Ω/km (at 20 °C) |
| Insulation resistance | ≥ 20 MΩ*km |
| Nominal voltage, cable | 300 V |
| Test voltage | 1200 V |
| Smallest bending radius, fixed installation | 63 mm |
| Flame resistance | according to DIN VDE 0482 |
| | According to DIN EN 50265-2-1 |
| | in acc. with UL FT-2 |
| Ambient temperature (operation) | -5 °C ... 80 °C (Cable, flexible installation) |
| | -40 °C ... 80 °C (cable, fixed installation) |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------------------|
| Degree of protection | IP65 |
| | IP67 |
| Ambient temperature (operation) | -25 °C ... 85 °C (valve plug) |

SAC- 1,5/0,1-116/2XBI-1L-Z - Double valve connector cable



1458347

<https://www.phoenixcontact.com/us/products/1458347>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27060312 |
| ECLASS-12.0 | 27060312 |
| ECLASS-13.0 | 27060312 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31251500 |
|-------------|----------|

SAC- 1,5/0,1-116/2XBI-1L-Z - Double valve connector cable



1458347

<https://www.phoenixcontact.com/us/products/1458347>

Environmental product compliance

| | |
|------------|--|
| China RoHS | Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |
|------------|--|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com