

SACB-4/ 8-L-C GG SCO - Sensor/actuator box header



1516739

<https://www.phoenixcontact.com/us/products/1516739>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator box header, application: Standard, connection method: M12-SPEEDCON-socket Metal, number of slots: 4, number of positions: 5, coding: A, slot assignment: Double, status display: Yes, pnp; master cable connection: Pluggable screw connection, shielding: no

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1516739 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF42 |
| Product key | BF3CCD |
| Catalog page | Page 265 (C-2-2019) |
| GTIN | 4017918967468 |
| Weight per piece (including packing) | 197.6 g |
| Weight per piece (excluding packing) | 175.5 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

SACB-4/ 8-L-C GG SCO - Sensor/actuator box header



1516739
<https://www.phoenixcontact.com/us/products/1516739>

Technical data

Notes

| | |
|---------|--|
| General | NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties. |
| General | Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories". |

Product properties

| | |
|---------------------|--------------------------------------|
| Product type | Header with metric measurement slots |
| Number of positions | 5 |
| Application | Standard |
| Number of slots | 4 |
| Coding | A |
| LED | yes |

System properties

| | |
|------------------------|---------------------------|
| Local diagnostics | |
| Monitored function | Supply voltage per module |
| Optical representation | Green LED |


Electrical properties

| | |
|---|-------------------------------------|
| Max. operating voltage U_{max} | 30 V DC |
| Local diagnostics | Supply voltage per module Green LED |
| | Status display I/O Yellow LED |
| Nominal voltage U_N | 24 V DC |
| Rated current, total | 10 A |
| | 2x 8 A (For electrical isolation) |
| Max. current carrying capacity per path | 2 A |
| Current carrying capacity per slot | 4 A |

Signaling

| | |
|------------------------|-----|
| Status display present | Yes |
|------------------------|-----|

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 58 mm |

SACB-4/ 8-L-C GG SCO - Sensor/actuator box header



1516739

<https://www.phoenixcontact.com/us/products/1516739>

| | |
|--------|--------|
| Height | 26 mm |
| Length | 117 mm |

Material specifications

| | |
|--|---------------|
| Material Threaded sleeve | Die-cast zinc |
| Material Housing | PBT |
| Material Molding compound | PUR |
| Flammability rating according to UL 94 | V0 |
| Seal material O-ring | NBR |
| Contact material | Cu alloy |
| Contact surface material | gold-plated |
| Contact carrier material | PA |
| Material of contact, master cable side | CU alloy |
| Material of the contact carrier on the master cable side | PA 6.6 V0 |
| Material of contact surface, master cable side | gold-plated |

Cable/line

| | |
|-------------------|----------------------------|
| Connection method | Pluggable screw connection |
|-------------------|----------------------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Degree of protection | IP65 |
| | IP67 |
| | IP69K |
| Ambient temperature (operation) | -30 °C ... 80 °C |

Standards and regulations

| | |
|--------------------------|-----------------|
| Standard designation | M12 connector |
| Standards/specifications | IEC 61076-2-101 |

SACB-4/ 8-L-C GG SCO - Sensor/actuator box header



1516739

<https://www.phoenixcontact.com/us/products/1516739>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440111 |
| ECLASS-12.0 | 27440111 |
| ECLASS-13.0 | 27440111 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC003558 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 31251500 |
|-------------|----------|



Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com