

# SACC-MINFS-3CON-PG 9 - Connector



1521300  
<https://www.phoenixcontact.com/us/products/1521300>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector, Universal, 3-position, Socket straight 7/8"-16UNF, coding: A, Screw connection, knurl material: Zinc die-cast, nickel-plated, cable gland Pg9, external cable diameter 6 mm ... 8 mm

## Your advantages

- Safe use in the field, thanks to a high degree of protection
- Screw connection: proven connection technology for a large selection of different conductors

## Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 1521300            |
| Packing unit                         | 1 pc               |
| Minimum order quantity               | 1 pc               |
| Sales key                            | BF30               |
| Product key                          | BF2FAA             |
| Catalog page                         | Page 25 (C-2-2017) |
| GTIN                                 | 4017918949532      |
| Weight per piece (including packing) | 45.33 g            |
| Weight per piece (excluding packing) | 43.3 g             |
| Customs tariff number                | 85366990           |
| Country of origin                    | DE                 |

# SACC-MINFS-3CON-PG 9 - Connector



1521300

<https://www.phoenixcontact.com/us/products/1521300>

## Technical data

### Notes

#### General

**NOTE:** Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

### Mounting

#### Assembly instructions

The wires can be connected both with ferrules and without ferrules

### Product properties


|                      |                                 |
|----------------------|---------------------------------|
| Product type         | Circular connector (cable-side) |
| Sensor type          | Universal                       |
| Number of positions  | 3                               |
| No. of cable outlets | 1                               |
| Shielded             | no                              |
| Coding               | A                               |
| Cable outlet         | straight                        |
| Pg screw connection  | Pg9                             |

#### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Dimensions

#### Dimensional drawing



|        |         |
|--------|---------|
| Width  | 27 mm   |
| Height | 27 mm   |
| Length | 78.5 mm |

#### External dimensions

|                  |               |
|------------------|---------------|
| Outside diameter | 6 mm ... 8 mm |
|------------------|---------------|

#### Housing

|                  |       |
|------------------|-------|
| Diameter housing | 27 mm |
|------------------|-------|

### Material specifications

|                                        |      |
|----------------------------------------|------|
| Flammability rating according to UL 94 | HB   |
| Material of grip body                  | PBT  |
| Contact material                       | CuZn |
| Contact surface material               | Au   |

# SACC-MINFS-3CON-PG 9 - Connector



1521300

<https://www.phoenixcontact.com/us/products/1521300>

|                               |                              |
|-------------------------------|------------------------------|
| Contact carrier material      | PUR/PA 6.6                   |
| Material for screw connection | Zinc die-cast, nickel-plated |

## Connection data

### Conductor connection

|                                         |                                                                |
|-----------------------------------------|----------------------------------------------------------------|
| Connection method                       | Screw connection                                               |
| Connection cross section                | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (without ferrule) |
|                                         | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (with ferrule)    |
|                                         | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (solid)           |
| Connection cross section AWG            | 22 ... 16 (without ferrule)                                    |
|                                         | 22 ... 16 (with ferrule)                                       |
| Stripping length of the individual wire | 7 mm                                                           |
| Tightening torque                       | 0.8 Nm (7/8" connectors)                                       |
|                                         | 0.4 Nm (Screw terminal blocks)                                 |
|                                         | 0.8 Nm ... 1 Nm (Pressure screw)                               |

## Electrical properties

|                                |          |
|--------------------------------|----------|
| Rated surge voltage            | 4 kV     |
| Contact resistance             | ≤ 5 mΩ   |
| Insulation resistance          | ≥ 100 MΩ |
| Nominal voltage U <sub>N</sub> | 300 V AC |
|                                | 300 V DC |
| Nominal current I <sub>N</sub> | 12 A     |

## Mechanical properties

### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 100 |
|-----------------------------|-------|

## Connector

### Connection 1

|                   |            |
|-------------------|------------|
| Head design       | Socket     |
| Head cable outlet | straight   |
| Head thread type  | 7/8"-16UNF |
| Coding            | A          |

## Cable/line

|                                         |           |
|-----------------------------------------|-----------|
| Signal type/category                    | Universal |
| Stripping length of the individual wire | 7 mm      |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP67                             |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |

# SACC-MINFS-3CON-PG 9 - Connector



1521300

<https://www.phoenixcontact.com/us/products/1521300>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SACC-MINFS-3CON-PG 9 - Connector



1521300  
<https://www.phoenixcontact.com/us/products/1521300>

## Environmental product compliance

|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                               |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                               |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)