

1521478

https://www.phoenixcontact.com/us/products/1521478

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector, Universal, 3-position, Socket angled 7/8"-16UNF, coding: A, Screw connection, knurl material: Zinc die-cast, nickel-plated, cable gland Pg9, external cable diameter 6 mm ... 8 mm

## Your advantages

- · Safe use in the field, thanks to a high degree of protection
- · Screw connection: proven connection technology for a large selection of different conductors

#### Commercial data

Item number	1521478
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF30
Product key	BF2FAA
Catalog page	Page 25 (C-2-2017)
GTIN	4017918949693
Weight per piece (including packing)	49.96 g
Weight per piece (excluding packing)	42.9 g
Customs tariff number	85366990
Country of origin	DE



1521478

https://www.phoenixcontact.com/us/products/1521478

## Technical data

#### Notes

	General	NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.
--	---------	---

### Mounting

Assembly instructions	The wires can be connected both with ferrules and without ferrules
	The connector pin assignment can be rotated 45° to the cable outlet


### Product properties

Universal
3
1
no
A
angled
Pg9

#### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

#### **Dimensions**



### Material specifications



https://www.phoenixcontact.com/us/products/1521478



Flammability rating according to UL 94	НВ
Material of grip body	PBT
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PUR/PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

#### Connection data

#### Conductor connection

Connection method	Screw connection
Connection cross section	0.34 mm <sup>2</sup> 1.5 mm <sup>2</sup> (without ferrule)
	0.34 mm <sup>2</sup> 1.5 mm <sup>2</sup> (with ferrule)
	0.34 mm <sup>2</sup> 1.5 mm <sup>2</sup> (solid)
Connection cross section AWG	22 16 (without ferrule)
	22 16 (with ferrule)
Stripping length of the individual wire	7 mm
Tightening torque	0.8 Nm (7/8" connectors)
	0.4 Nm (Screw terminal blocks)
	0.8 Nm 1 Nm (Pressure screw)

### Electrical properties

Rated surge voltage	4 kV
Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage U <sub>N</sub>	300 V AC
	300 V DC
Nominal current I <sub>N</sub>	12 A

#### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	≥ 100

#### Connector

#### Connection 1

Head design	Socket
Head cable outlet	angled
Head thread type	7/8"-16UNF
Coding	A

#### Cable/line

Signal type/category	Universal
Stripping length of the individual wire	7 mm



1521478

https://www.phoenixcontact.com/us/products/1521478

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)



1521478

https://www.phoenixcontact.com/us/products/1521478

# Classifications

#### **ECLASS**

	ECLASS-11.0	27440102	
	ECLASS-12.0	27440116	
	ECLASS-13.0	27440116	
ETIM			
	ETIM 9.0	EC002635	
UNSPSC			
	UNSPSC 21.0	39121400	



1521478

https://www.phoenixcontact.com/us/products/1521478

## Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com