

1539156

<https://www.phoenixcontact.com/us/products/1539156>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Master cable ring, application: Distributor boxes, number of positions: 19, shielding: yes



Commercial data

Item number	1539156
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF45
Product key	BF3ZBX
Catalog page	Page 305 (C-2-2019)
GTIN	4046356076357
Weight per piece (including packing)	11,586 g
Weight per piece (excluding packing)	11,586 g
Customs tariff number	85444290
Country of origin	DE

# SACB-16X0,5/3X1,0-50 PUR SH - Master cable ring



1539156

<https://www.phoenixcontact.com/us/products/1539156>

## Technical data

### Product properties


Product type	Cable by the meter
Number of positions	19
Application	Distributor boxes
LED	No

### Electrical properties

Nominal voltage $U_N$	300 V AC
	300 V DC

### Cable/line

PUR/PVC shielded, black [PUR]

Dimensional drawing	
Number of positions	19
Shielded	yes
Cable type	PUR/PVC shielded, black [PUR]
Conductor structure signal line	64x 0.10 mm
AWG signal line	20
Conductor cross section	16x 0.5 mm <sup>2</sup> (Signal line) 3x 1 mm <sup>2</sup> (Power supply)
External cable diameter	11.60 mm ±0.3 mm
Outer sheath, material	PUR
External sheath, color	deep black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red, black, violet, gray/pink, red/blue, white/green, brown/green, white/yellow, yellow/brown, white/gray, gray/brown
Overall twist	Wires twisted in layers
Nominal voltage, cable	300 V
Test voltage	2000 V
Max. bending cycles	1500000
Flame resistance	DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803

# SACB-16X0,5/3X1,0-50 PUR SH - Master cable ring



1539156

<https://www.phoenixcontact.com/us/products/1539156>

Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free
	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation)
	-5 °C ... 80 °C (Cable, flexible installation)

# SACB-16X0,5/3X1,0-50 PUR SH - Master cable ring



1539156

<https://www.phoenixcontact.com/us/products/1539156>

## Classifications

### ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

### ETIM

ETIM 9.0	EC003250
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SACB-16X0,5/3X1,0-50 PUR SH - Master cable ring



1539156

<https://www.phoenixcontact.com/us/products/1539156>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)