RC-12P1N8D0000 - Contact insert

1597635

https://www.phoenixcontact.com/us/products/1597635

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert, M23, number of positions: 12, contact connection type: Pin, Crimp connection, series: NC, RC, RM, TU, UC, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240864

Commercial data

| Item number | 1597635 |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB31 |
| Product key | ABRAFU |
| GTIN | 4046356217217 |
| Weight per piece (including packing) | 10 g |
| Weight per piece (excluding packing) | 4.88 g |
| Customs tariff number | 85389099 |
| Country of origin | DE |

RC-12P1N8D0000 - Contact insert

1597635

https://www.phoenixcontact.com/us/products/1597635

Technical data

Product properties

| Product type | Contact insert |
|---------------------|----------------|
| Number of positions | 12 |
| Connection profile | 12 |
| Application | Signal |
| Series | NC |
| | RC |
| | RM |
| | Т |
| | UC |
| Coding | Ν |
| Thread type | M23 |

Electrical properties

| Contact | |
|--------------------------------|-----------------|
| Contact diameter | 1 mm |
| Min. cross section | 0.14 mm² |
| Max. cross section | 0.56 mm² |
| Max. current | 8 A |
| Nominal voltage U _N | 48 V AC 74 V DC |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Rated surge voltage | 1.5 kV |

Connection data

Material specifications

| Insulator material | PA66 |
|--------------------|-----------------------------|
| Contact material | CuZn |
| Contact surface | Nickel-plated, gold coating |

Connector

| Direction of rotation | Standard |
|-----------------------|----------|
| | |

Mechanical properties

Mechanical data

Insertion/withdrawal cycles

50

Environmental and real-life conditions

PHŒNIX CONTACT



1597635

https://www.phoenixcontact.com/us/products/1597635



| Ambient conditions | |
|--|-------------|
| Ambient temperature (storage/transport) | 15 °C 25 °C |
| Permissible humidity (storage/transport) | 50 % 65 % |



1597635

https://www.phoenixcontact.com/us/products/1597635



Classifications

ECLASS

| ECLASS-12.0 27440223 | |
|----------------------|--|
| ECLASS-13.0 27440223 | |

ETIM

| | ETIM 9.0 | EC003557 |
|--------|-------------|----------|
| UNSPSC | | |
| | UNSPSC 21.0 | 39121400 |



1597635

https://www.phoenixcontact.com/us/products/1597635



Environmental product compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|---|
| | |
| | |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com