

SF-7EE1N8AS000 - Pin/socket, panel feed-through



1605567

<https://www.phoenixcontact.com/us/products/1605567>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pin/socket, panel feed-through, straight, M23, M23, number of positions: 4+3+PE, contact connection type: Socket/pin, Axial O-ring, 4xM3, shielded: yes, degree of protection: IP67, cable diameter range: 0 mm ... 0 mm, number of positions: 8, connection method: Crimp connection, series: SF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241924

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1605567 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | AB32 |
| Product key | ABRBFJ |
| Catalog page | Page 159 (C-2-2019) |
| GTIN | 4046356253635 |
| Weight per piece (including packing) | 192.53 g |
| Weight per piece (excluding packing) | 192.53 g |
| Customs tariff number | 85444290 |
| Country of origin | DE |

Technical data

Notes

Safety note

Safety note

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.

- The products are suitable for applications in plant, controller, and electrical device engineering.

- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.

- Assembled products may not be manipulated or improperly opened.

- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)).

- When using the product in direct connection with third-party manufacturers, the user is responsible.

- For operating voltages > 50 V AC, conductive connector housings must be grounded

- Ensure that the protective or functional ground has been properly connected.

- VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector

- Only use tools recommended by Phoenix Contact

- The installation notes/Design In documents online on the download page at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) must be observed for this product.

- Operate the connector only when it is fully plugged in and interlocked.

- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.

- Observe the minimum bending radius of the cable. Lay the cable without twisting it.

- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

SF-7EE1N8AS000 - Pin/socket, panel feed-through



1605567

<https://www.phoenixcontact.com/us/products/1605567>

Mounting

| | |
|----------|-------|
| Mounting | 4x M3 |
|----------|-------|

Product properties

| | |
|---------------------|-----------------------------------|
| Product type | Circular connectors (device side) |
| Number of positions | 8 |
| Connection profile | 4+3+PE |
| Application | Power |
| Series | SF |
| Shielded | yes |
| Coding | N |
| Thread type | M23 |

Material specifications

| | |
|----------------------------|--|
| Seal material | FPM |
| Housing material | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Insulator material | PA 6.6 |
| Gasket and O-ring material | FPM |

Electrical properties

Contact

| | |
|-----------------------|-------|
| Max. current | 30 A |
| Nominal voltage U_N | 630 V |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Rated surge voltage | 4 kV |

Contact

| | |
|-----------------------|-------|
| Max. current | 9 A |
| Nominal voltage U_N | 250 V |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Rated surge voltage | 6 kV |

Connection data

Conductor connection

| | |
|-------------------------|------------------|
| Connection method | Crimp connection |
| Contact connection type | Socket/pin |

Connector

| | |
|------|----------|
| Type | straight |
|------|----------|

Connection 1

SF-7EE1N8AS000 - Pin/socket, panel feed-through



1605567

<https://www.phoenixcontact.com/us/products/1605567>

| | |
|-------------|--------|
| Head design | Socket |
|-------------|--------|

Connection 2

| | |
|-------------|------|
| Head design | Plug |
|-------------|------|

Cable/line

| | |
|-------------------------|---------------|
| External cable diameter | 0 mm ... 0 mm |
|-------------------------|---------------|

Environmental and real-life conditions

Ambient conditions

| | |
|--|-------------------|
| Degree of protection | IP67 |
| Ambient temperature (operation) | -40 °C ... 125 °C |
| Ambient temperature (storage/transport) | 15 °C ... 25 °C |
| Altitude | 3000 m |
| Permissible humidity (storage/transport) | 50 % ... 65 % |

SF-7EE1N8AS000 - Pin/socket, panel feed-through



1605567

<https://www.phoenixcontact.com/us/products/1605567>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

SF-7EE1N8AS000 - Pin/socket, panel feed-through



1605567

<https://www.phoenixcontact.com/us/products/1605567>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com