

https://www.phoenixcontact.com/us/products/1607729



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 27 ... 34 mm, WAF 50, screw connection: M40

Commercial data

| Item number | 1607729 |
|--------------------------------------|---------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BF68 |
| Product key | BF7DAX |
| Catalog page | Page 690 (C-4-2015) |
| GTIN | 4017918938819 |
| Weight per piece (including packing) | 184.2 g |
| Weight per piece (excluding packing) | 168.65 g |
| Customs tariff number | 74198090 |
| Country of origin | DE |



https://www.phoenixcontact.com/us/products/1607729



Technical data

Product properties

| Product type | Full screw connection |
|------------------------------|-----------------------|
| No. of conductors | 1 |
| Type of the screw connection | M40 |
| Manufacturer | Jacob |
| Manufacturer Designation | 101036M40 |
| Shielded | no |

Dimensions

| Dimensional drawing | -95 -0 -0 -0 -0 -0 -0 -0 -0 -0 -0 -0 -0 -0 |
|---------------------------------|---|
| Length | 35 mm |
| Length of the connecting thread | 8 mm |
| Hole diameter | 40.1 mm 40.3 mm |
| Wrench size, union nut | 50 mm |
| Wrench size, support | 50 mm |
| Hexagon angular dimension | 58 mm |
| Thread type connection side | M40 x 1.5 |
| Thread pitch | 1.5 mm |

Connection data

| Tightening torque | 20 Nm (Union nut) |
|-------------------|------------------------|
| | 20 Nm (Support sleeve) |

Material specifications

| Material Compression ring | PA |
|-------------------------------|----------------------|
| Seal material O-ring | NBR |
| Seal material Cable seal | Neoprene |
| Material for screw connection | Brass, nickel-plated |

Cable/line

| External cable diameter (Cable 1) | 27 mm 34 mm |
|-----------------------------------|-------------|
| Halogen-free | no |

Environmental and real-life conditions

Ambient conditions

| Degree of protection | IP68 (up to 5 bar) |
|---------------------------------|--------------------|
| Ambient temperature (operation) | -30 °C 100 °C |



1607729

https://www.phoenixcontact.com/us/products/1607729

Classifications

UNSPSC 21.0

ECLASS

| ECLASS-11.0 | 27144432 |
|-------------|----------|
| ECLASS-12.0 | 27140801 |
| ECLASS-13.0 | 27140801 |
| ETIM | |
| ETIM 9.0 | EC000441 |
| UNSPSC | |

39121300



https://www.phoenixcontact.com/us/products/1607729



Environmental product compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|--|
| | |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com