1607732

https://www.phoenixcontact.com/us/products/1607732



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Housing, Range of articles: VARIOCON, design: VC1, housing material: Zinc die-cast, surface bronzed and nickel-plated, color: gray

### Commercial data

Item number	1607732
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB01
Product key	ABLADB
GTIN	4017918952945
Weight per piece (including packing)	362.86 g
Weight per piece (excluding packing)	342 g
Customs tariff number	85369010
Country of origin	PL

1607732

https://www.phoenixcontact.com/us/products/1607732



### Technical data

#### Notes

Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	<ul> <li>WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li> </ul>
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	<ul> <li>The products are suitable for applications in plant, controller, and electrical device engineering.</li> </ul>
	<ul> <li>When operating the connectors in outdoor applications, they must be separately protected against environmental influences.</li> </ul>
	<ul> <li>Assembled products may not be manipulated or improperly opened.</li> </ul>
	<ul> <li>Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).</li> </ul>
	<ul> <li>When using the product in direct connection with third-party manufacturers, the user is responsible.</li> </ul>
	<ul> <li>For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li> </ul>
	<ul> <li>Ensure that the protective or functional ground has been properly connected.</li> </ul>
	VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	<ul> <li>Observe the corresponding technical data. You will find information:</li> <li>o On the product</li> <li>o On the packing label</li> <li>o In the supplied documentation</li> <li>o Online at phoenixcontact.com/products under the product</li> </ul>
	Only use tools recommended by Phoenix Contact
	<ul> <li>The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.</li> </ul>
	<ul> <li>Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products</li> </ul>
	Operate the connector only when it is fully plugged in.
	<ul> <li>Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the</li> </ul>

1607732

https://www.phoenixcontact.com/us/products/1607732



standa	irds.
	rve the minimum bending radius of the cable. Lay the without twisting it.
ambier warm ι	connector warms up in normal operation. Depending on the nt conditions, the surface of the connector can continue to up. In this case, the user is responsible for posting gs (e.g. DIN EN ISO 13732-1:2008-12).

#### Product properties

Туре	VC1
Product type	Panel mounting base
Product family	VARIOCON

#### Dimensions

Width	78 mm
Height	50 mm
Length	36 mm

#### Material specifications

Color	gray
Color of the housing part	gray
Material	Die-cast zinc
Flammability rating according to UL 94	VO
Seal material	EPDM, conductive
O-ring material	NBR
Housing material	Zinc die-cast, surface bronzed and nickel-plated

1607732

https://www.phoenixcontact.com/us/products/1607732



### Classifications

#### ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

#### ETIM

	ETIM 9.0	EC000437
UNSPSC		
	UNSPSC 21.0	31261500



1607732 https://www.phoenixcontact.com/us/products/1607732



### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com