

VS-PPC-F2-MSTB-MNNA-1R-SPSA5 - Panel mounting frames



1608249

<https://www.phoenixcontact.com/us/products/1608249>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Push/pull panel mounting frame, metal, version 14, including contact insert with spring-cage connection, fixed 24 V coding according to Guideline for PROFINET, for rectangular mounting cutout, with seal, without fixing screws

Commercial data

Item number	1608249
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB17
Product key	ABNOJA
Catalog page	Page 364 (C-2-2019)
GTIN	4046356160049
Weight per piece (including packing)	63.4 g
Weight per piece (excluding packing)	60 g
Customs tariff number	85366990
Country of origin	DE

VS-PPC-F2-MSTB-MNNA-1R-SPSA5 - Panel mounting frames

1608249

<https://www.phoenixcontact.com/us/products/1608249>

Technical data

Product properties

Type	D-SUB
Product type	Panel mounting frame
Number of positions	5
Application	Freenet
Type	Male

Insulation characteristics

Degree of pollution	2
---------------------	---

Electrical properties


Rated voltage (III/3)	24 V
Rated current	16 A (at 20 °C)
Transmission medium	Copper

Connection data

Connection technology

Connection method	Spring-cage connection
-------------------	------------------------

Dimensions

Dimensional drawing	
Width	36.2 mm
Height	42 mm
Length	41.9 mm

Material specifications

Color	silver
Material	Metal
Flammability rating according to UL 94	V0
Seal material	NBR
Seal material	NBR
Housing surface material	nickel-plated
Contact surface material	Au/Ni
Housing material	Metal

Mechanical properties

VS-PPC-F2-MSTB-MNNA-1R-SPSA5 - Panel mounting frames



1608249

<https://www.phoenixcontact.com/us/products/1608249>

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65/IP67
Ambient temperature (operation)	-40 °C ... 70 °C

Mounting

Mounting type	Front mounting
---------------	----------------

VS-PPC-F2-MSTB-MNNA-1R-SPSA5 - Panel mounting frames



1608249

<https://www.phoenixcontact.com/us/products/1608249>

Classifications

ECLASS

ECLASS-11.0	27440210
ECLASS-12.0	27440210
ECLASS-13.0	27440210

ETIM

ETIM 9.0	EC002310
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-PPC-F2-MSTB-MNNA-1R-SPSA5 - Panel mounting frames



1608249

<https://www.phoenixcontact.com/us/products/1608249>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com