

K-17-M23 M9/5,0-E01/M23 F8 - Connector in molded plastic on both sides



1619296

<https://www.phoenixcontact.com/us/products/1619296>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector in molded plastic on both sides, Straight, plastic molded, Straight, plastic molded, cable length: 5 m, shielded: yes, color of outer sheath: green

Your advantages

- Our standard: robust halogen-free PUR cable
- Simple and safe: 100% electrically tested and assembled ready for use
- Designs with preassembled cables on one or both sides
- High flexibility: customer-specific assemblies and cable lengths can be supplied

Commercial data

Item number	1619296
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB34
Product key	ABRDFG
Catalog page	Page 217 (C-2-2019)
GTIN	4046356835152
Weight per piece (including packing)	790 g
Weight per piece (excluding packing)	790 g
Customs tariff number	85444290
Country of origin	DE

K-17-M23 M9/5,0-E01/M23 F8 - Connector in molded plastic on both sides



1619296

<https://www.phoenixcontact.com/us/products/1619296>

Technical data

Product properties

Product type	Signal and power cable
--------------	------------------------

Connector

Connector specifications

Type	Straight, plastic molded
------	--------------------------

Cable specifications

Cable type	SSLC11Y
Shielded	yes
Cable structure	3 x 2 x 0.14 mm ² + 2 x 0.5 mm ² + 4 x 0.14 mm ² + 4 x 0.22 mm ²
Cable structure (AWG)	26 AWG/3pr + 20 AWG/2c + 26 AWG/4c + 24 AWG/4c
External cable diameter	9.40 mm
Outer sheath, material	TPU
Material wire insulation	TPU
External sheath, color	green
Nominal voltage, cable	30 V
Test voltage	0.5 kV
Rated current	9 A
Smallest bending radius, fixed installation	38 mm
Smallest bending radius, movable installation	94 mm
Ambient temperature (operation) for fixed installation	-30 °C ... 80 °C
Ambient temperature (operation) for flexible installation	-30 °C ... 60 °C

Connector specifications (second page)

Type	Straight, plastic molded
------	--------------------------

Electrical properties

Nominal current I _N	9 A
--------------------------------	-----

Cable/line

Cable length	5 m
--------------	-----

K-17-M23 M9/5,0-E01/M23 F8 - Connector in molded plastic on both sides



1619296

<https://www.phoenixcontact.com/us/products/1619296>

Classifications

ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

ETIM

ETIM 9.0	EC003250
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

K-17-M23 M9/5,0-E01/M23 F8 - Connector in molded plastic on both sides



1619296

<https://www.phoenixcontact.com/us/products/1619296>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com