

HC-B 16-A-DT-PEL-F - Terminal adapter



1648432

<https://www.phoenixcontact.com/us/products/1648432>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

HEAVYCON terminal adapter socket insert, B16 series, 16-pos., for the left side of the control cabinet, push-in connection



Your advantages

- Easy installation without tools, even when mounted, with push-in connection technology
- Shortest installation time compared to other connection technologies
- Quick and effortless wiring, in particular when space is tight
- Automatic cabling with robots possible
- Safe wiring and operation with color-coded actuators
- Shock and vibration-resistant in accordance with DIN EN 61373

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1648432 |
| Packing unit | 5 pc |
| Minimum order quantity | 5 pc |
| Sales key | BF61 |
| Product key | BF7ADC |
| Catalog page | Page 549 (C-2-2019) |
| GTIN | 4046356092159 |
| Weight per piece (including packing) | 137.61 g |
| Weight per piece (excluding packing) | 136.95 g |
| Customs tariff number | 85366990 |
| Country of origin | CN |

HC-B 16-A-DT-PEL-F - Terminal adapter



1648432

<https://www.phoenixcontact.com/us/products/1648432>

Technical data

Notes

| | |
|---------|---|
| General | For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B16 type |
| General | Connectors may be operated only when there is no load/voltage. |

Product properties

| | |
|---------------------|--|
| Type | B16 |
| Product type | Terminal adapter |
| Product family | HC-B |
| Number of positions | 16 |
| Connection profile | 16+PE |
| Contact numbering | 1 - 16 |
| Type | for the left side of the control cabinet |
| Series | HC-B |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|-----------------------|----------------|
| Rated voltage (III/3) | 500 V |
| Rated surge voltage | 6 kV |
| Rated current | 16 A |
| SCCR | 5 kA (UL 2237) |

Connection data

Connection technology

| | |
|-----------------------|--------------------|
| Connection technology | Push-in connection |
|-----------------------|--------------------|

Conductor connection

| | |
|---|---|
| Conductor cross section | 0.5 mm ² ... 2.5 mm ² |
| Connection cross section AWG | 22 ... 12 |
| Stripping length of the individual wire | 10 mm (13 mm with ferrule) |


Dimensions

HC-B 16-A-DT-PEL-F - Terminal adapter



1648432

<https://www.phoenixcontact.com/us/products/1648432>

| | |
|---------------------------------|---|
| Dimensional drawing |  |
| Width | 34 mm |
| Height | 72.1 mm |
| Length | 84 mm |
| Drill hole distance, horizontal | 77.5 mm |
| Drill hole distance, vertical | 27 mm |

Material specifications

| | |
|--|---|
| Flammability rating according to UL 94 | V0 |
| Contact material | Copper alloy |
| Contact surface material | Ag |
| Contact carrier material | PA |
| Standards/regulations | PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3) |

Cable/line

| | |
|---|----------------------------|
| Stripping length of the individual wire | 10 mm (13 mm with ferrule) |
|---|----------------------------|

Mechanical properties

Mechanical data

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 500 |
|-----------------------------|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 125 °C |

Standards and regulations

| | |
|--|--------------|
| Constructional and testing regulations | DIN EN 61984 |
| | DIN EN 60664 |
| | IEC 60352 |
| Tests | DIN EN 61984 |
| | DIN EN 60664 |
| | IEC 60352 |

Testing

HC-B 16-A-DT-PEL-F - Terminal adapter



1648432

<https://www.phoenixcontact.com/us/products/1648432>

Standards/regulations

PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Mounting

Assembly instructions

To ensure correct use, installation in housing with IP54 protection or better is required

Connectors may be plugged in only when there is no load/voltage.

HC-B 16-A-DT-PEL-F - Terminal adapter



1648432

<https://www.phoenixcontact.com/us/products/1648432>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440222 |
| ECLASS-12.0 | 27440222 |
| ECLASS-13.0 | 27440222 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000438 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121500 |
|-------------|----------|

HC-B 16-A-DT-PEL-F - Terminal adapter



1648432

<https://www.phoenixcontact.com/us/products/1648432>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com