

# VS-09-PROFIBUS-SP - D-SUB connector



1654345

<https://www.phoenixcontact.com/us/products/1654345>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



D-SUB connector, degree of protection: IP67, number of positions: 9, material: Plastic, connection method: Spring-cage connection, connection cross section: AWG 26- 16, cable outlet: angled, housing size: 1, color: gray, PROFIBUS

## Your advantages

- EMC protection
- Switchable termination resistor

## Commercial data

Item number	1654345
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB19
Product key	ABNCBA
Catalog page	Page 444 (C-2-2019)
GTIN	4017918970628
Weight per piece (including packing)	93.8 g
Weight per piece (excluding packing)	93.8 g
Customs tariff number	85369010
Country of origin	DE

## Technical data

### Notes

#### Safety note

##### Safety note

**WARNING:** The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- **WARNING:** Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

- **WARNING:** Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.

- The products are suitable for applications in plant, controller, and electrical device engineering.

- When operating the connectors in outdoor applications, they must be separately protected against environmental influences.

- Assembled products may not be manipulated or improperly opened.

- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)).

- When using the product in direct connection with third-party manufacturers, the user is responsible.

- For operating voltages > 50 V AC, conductive connector housings must be grounded

- Only use tools recommended by Phoenix Contact

- The installation notes/Design In documents online on the download page at [phoenixcontact.com/products](https://www.phoenixcontact.com/products) must be observed for this product.

- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at [phoenixcontact.com/products](https://www.phoenixcontact.com/products)

- Operate the connector only when it is fully plugged in and interlocked.

- Operate the connector only when it is fully plugged in.

- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.

- Observe the minimum bending radius of the cable. Lay the cable without twisting it.

- VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector

### Product properties

# VS-09-PROFIBUS-SP - D-SUB connector



1654345

<https://www.phoenixcontact.com/us/products/1654345>

Type	D-SUB
Product type	Data connector (cable side)
Sensor type	PROFIBUS
Number of positions	9
Connection profile	D-SUB
Application	PROFIBUS
No. of cable outlets	2
Type	Male
Shielded	yes
Cable outlet	angled

## Insulation characteristics

Overvoltage category	II
Degree of pollution	2

## Electrical properties

Rated voltage (III/3)	50 V
Rated surge voltage	0.5 kV
Rated current	1 A
Transmission medium	Copper

## Connection data

### Connection technology

Connection method	Spring-cage connection
Connection cross section AWG	26 ... 16 (solid)
	26 ... 18 (flexible)
Conductor cross section	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> (solid)
	0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup> (flexible)

## Material specifications

Color	gray
Flammability rating according to UL 94	V0
Cable seal material	CR/NBR
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	PBTP
Housing material	Plastic

## Cable/line

External cable diameter ( )	5 mm ... 9 mm
Stripping length of the individual wire	7.5 mm
Cable cross section	0.2 mm <sup>2</sup>

## Mechanical properties

# VS-09-PROFIBUS-SP - D-SUB connector



1654345

<https://www.phoenixcontact.com/us/products/1654345>

## Mechanical data

Insertion/withdrawal cycles	≥ 200
-----------------------------	-------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-20 °C ... 75 °C

# VS-09-PROFIBUS-SP - D-SUB connector



1654345

<https://www.phoenixcontact.com/us/products/1654345>

## Classifications

### ECLASS

ECLASS-11.0	27440302
ECLASS-13.0	27440302
ECLASS-12.0	27440302

### ETIM

ETIM 9.0	EC001132
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# VS-09-PROFIBUS-SP - D-SUB connector



1654345

<https://www.phoenixcontact.com/us/products/1654345>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)