

VS-15-BU-DSUB-LH-B - D-SUB contact insert



1654811

<https://www.phoenixcontact.com/us/products/1654811>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 2, with 15 signal contacts, type of contact socket, for PCB assembly, angled, fixing with a 2.5 mm hole and solder metal plate, for panel mounting frame VS-15-...



Your advantages

- D-SUB 15 connection
- Easy assembly
- Direct PCB connection
- Compatible with IP67 panel-mount frame

Commercial data

Item number	1654811
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	AB19
Product key	ABNCAB
Catalog page	Page 211 (C-2-2013)
GTIN	4017918989200
Weight per piece (including packing)	13.08 g
Weight per piece (excluding packing)	13.08 g
Customs tariff number	85369010
Country of origin	DE

VS-15-BU-DSUB-LH-B - D-SUB contact insert



1654811

<https://www.phoenixcontact.com/us/products/1654811>

Technical data

Product properties

Type	D-SUB
Product type	Female insert
Number of positions	15
Connection profile	D-SUB
Number of slots	1
Type	Socket
Shielded	yes

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties


Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1200 V
Transmission medium	Copper
Power transmission	Power

Connection data

Connection technology

Connection method	Wave soldering contacts
-------------------	-------------------------

Dimensions

Dimensional drawing	
Width	20.2 mm
Height	12.93 mm
Length	39.52 mm

Material specifications

Flammability rating according to UL 94	V0
Housing surface material	metal-plated
Contact material	Copper alloy
Contact surface material	Gold

VS-15-BU-DSUB-LH-B - D-SUB contact insert



1654811

<https://www.phoenixcontact.com/us/products/1654811>

Contact carrier material	PBT-GF
Housing material	Metal

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 200
Insertion force per signal contact	$\leq 3.40 \text{ N}$

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

Mounting

Mounting type	PCB mounting
---------------	--------------

VS-15-BU-DSUB-LH-B - D-SUB contact insert



1654811

<https://www.phoenixcontact.com/us/products/1654811>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

ETIM

ETIM 9.0	EC003557
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-15-BU-DSUB-LH-B - D-SUB contact insert



1654811

<https://www.phoenixcontact.com/us/products/1654811>

Environmental product compliance

REACH SVHC

Lead 7439-92-1

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com