

# VS-25-ST-DSUB-LH-B - D-SUB contact insert



1654824

<https://www.phoenixcontact.com/us/products/1654824>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 3, with 25 signal contacts, type of contact pin, for PCB assembly, angled, fixing with a 2.5 mm hole and solder metal plate, for panel mounting frame VS-25-...



## Your advantages

- D-SUB 25 connection
- Easy assembly
- Direct PCB connection
- Compatible with IP67 panel-mount frame

## Commercial data

Item number	1654824
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	AB19
Product key	ABNCAA
Catalog page	Page 211 (C-2-2013)
GTIN	4017918989217
Weight per piece (including packing)	16.134 g
Weight per piece (excluding packing)	14.11 g
Customs tariff number	85366990
Country of origin	DE

# VS-25-ST-DSUB-LH-B - D-SUB contact insert

1654824

<https://www.phoenixcontact.com/us/products/1654824>

## Technical data

### Product properties

Type	D-SUB
Product type	Male insert
Number of positions	25
Connection profile	D-SUB 25
Type	Male
Shielded	no

### Insulation characteristics

Overvoltage category	III
Degree of pollution	2


### Electrical properties

Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1200 V
Transmission medium	Copper

### Connection data

Connection method	PCB connection
-------------------	----------------

### Dimensions

Dimensional drawing	
Width	53 mm
Height	12.5 mm
Length	14 mm

### Material specifications

Flammability rating according to UL 94	V0
Housing surface material	tin-plated
Contact material	Copper alloy
Contact surface material	Au
Housing material	Steel, tin-plated

### Mechanical properties

#### Mechanical data

# VS-25-ST-DSUB-LH-B - D-SUB contact insert



1654824

<https://www.phoenixcontact.com/us/products/1654824>

Insertion/withdrawal cycles	$\geq 200$
Insertion force per signal contact	$\leq 3.40 \text{ N}$

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

## Mounting

Mounting type	Hole and solder metal plate
---------------	-----------------------------

# VS-25-ST-DSUB-LH-B - D-SUB contact insert



1654824

<https://www.phoenixcontact.com/us/products/1654824>

## Classifications

### ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

### ETIM

ETIM 9.0	EC003557
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# VS-25-ST-DSUB-LH-B - D-SUB contact insert



1654824

<https://www.phoenixcontact.com/us/products/1654824>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)