

VS-15-ST-DSUB-3P-LH - D-SUB contact support



1655331

<https://www.phoenixcontact.com/us/products/1655331>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact carrier, shell size 2, accommodation for 3 combined contacts, type of contact pin, fixing with 4-40 UNC thread and solder pins, for panel mounting frame VS-15-...



Your advantages

- Compatible with IP67 sleeve housing and panel-mount frame
- Easy assembly

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1655331 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | AB19 |
| Product key | ABNCAA |
| Catalog page | Page 214 (C-2-2013) |
| GTIN | 4046356029278 |
| Weight per piece (including packing) | 14.46 g |
| Weight per piece (excluding packing) | 10.99 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

Technical data

Notes

| | |
|---------|--|
| General | The contacts must be ordered separately since they are not included in the scope of supply of the combi contact inserts. |
|---------|--|

Product properties

| | |
|---------------------|----------------------------|
| Type | D-SUB |
| Product type | Male insert |
| Number of positions | 3 |
| Connection profile | D-SUB |
| Application | Combination contact insert |
| Type | Male |
| Shielded | no |

Electrical properties

| | |
|---------------------|--------|
| Transmission medium | Copper |
|---------------------|--------|

Connection data

| | |
|-------------------|-------|
| Connection method | D-SUB |
|-------------------|-------|

Material specifications

| | |
|--|-------------------------|
| Flammability rating according to UL 94 | V0 |
| Contact material | Copper alloy |
| Contact surface material | Gold over nickel |
| Contact carrier material | PBTP |
| Housing material | Steel, yellow chromated |

Mechanical properties

Mechanical data

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 500 |
|-----------------------------|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -55 °C ... 125 °C |

Mounting

| | |
|---------------|-------------------------|
| Mounting type | Threads and solder pins |
|---------------|-------------------------|

VS-15-ST-DSUB-3P-LH - D-SUB contact support



1655331

<https://www.phoenixcontact.com/us/products/1655331>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440223 |
| ECLASS-12.0 | 27440223 |
| ECLASS-13.0 | 27440223 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC003557 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

VS-15-ST-DSUB-3P-LH - D-SUB contact support



1655331

<https://www.phoenixcontact.com/us/products/1655331>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com