

# VS-ST-KX-50-RG58 - D-SUB coaxial contact



1655580

<https://www.phoenixcontact.com/us/products/1655580>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coaxial contact, for D-SUB combination inserts, solder cup, socket, straight, for cable RG 58, gold-plated

## Commercial data

Item number	1655580
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAC
Catalog page	Page 325 (PC-2009)
GTIN	4046356029490
Weight per piece (including packing)	2.546 g
Weight per piece (excluding packing)	2.294 g
Customs tariff number	85366910
Country of origin	CZ

# VS-ST-KX-50-RG58 - D-SUB coaxial contact



1655580

<https://www.phoenixcontact.com/us/products/1655580>

## Technical data

### Product properties

Product type	Contacts
Type	Individual female contact
Contact material type	turned
Series	HC-M-04-KOAX


### Electrical properties

Maximum load current	2 A
Rated voltage (III/3)	250 V
Rated surge voltage	250 V
Rated current	2 A
Insulation resistance	10 TΩ
Wave impedance	50 Ω

### Connection data

Maximum load current	2 A
Connection method	Solder cup

### Dimensions

Dimensional drawing	
Length	26.8 mm

### Mechanical characteristics

Contact diameter	4.8 mm
------------------	--------

### Material specifications

Material	Metal
Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel

### Cable/line

External cable diameter ( )	5.2 mm
Wave impedance	50 Ω

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	≥ 500
Insertion force per signal contact	≤ 7.00 N

# VS-ST-KX-50-RG58 - D-SUB coaxial contact



1655580

<https://www.phoenixcontact.com/us/products/1655580>

Extraction force per signal contact	≤ 7 N
-------------------------------------	-------

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-55 °C ... 135 °C
---------------------------------	-------------------

## Mounting

Mounting type	Solder connection
---------------	-------------------

# VS-ST-KX-50-RG58 - D-SUB coaxial contact



1655580

<https://www.phoenixcontact.com/us/products/1655580>

## Classifications

### ECLASS

ECLASS-11.0	27440204
ECLASS-12.0	27440204
ECLASS-13.0	27440204

### ETIM

ETIM 9.0	EC000796
----------	----------

### UNSPSC

UNSPSC 21.0	39121500
-------------	----------

# VS-ST-KX-50-RG58 - D-SUB coaxial contact



1655580

<https://www.phoenixcontact.com/us/products/1655580>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)