

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector



1658008

<https://www.phoenixcontact.com/us/products/1658008>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: black, Ethernet

Your advantages

- Easy and time-saving assembly with IDC fast connection technology
- Can be used internationally due to EAC, UL 1863, and CAN/CSA C22.2
- Ideal companion for servicing or repairs in the field: no special tools required for mounting

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1658008 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB10 |
| Product key | ABNAAD |
| Catalog page | Page 372 (C-2-2019) |
| GTIN | 4046356138536 |
| Weight per piece (including packing) | 10.38 g |
| Weight per piece (excluding packing) | 10.3 g |
| Customs tariff number | 85366990 |
| Country of origin | CH |

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector



1658008

<https://www.phoenixcontact.com/us/products/1658008>

Technical data

Product properties

| | |
|----------------------|-----------------------------|
| Type | RJ45 |
| Product type | Data connector (cable side) |
| Sensor type | Ethernet |
| Number of positions | 8 |
| Connection profile | RJ45 |
| No. of cable outlets | 1 |
| Type | RJ45 |
| Shielded | yes |
| Cable outlet | straight |
| Positions/contacts | 8P8C |

Insulation characteristics

| | |
|----------------------|---|
| Overvoltage category | I |
| Degree of pollution | 2 |

Electrical properties

| | |
|---|--|
| Rated voltage (III/3) | 72 V (DC) |
| Rated surge voltage | 330 kV |
| Rated current | 1.75 A |
| Contact resistance | < 20 mΩ (Contact) < 100 mΩ (shield) |
| Frequency range | 100 MHz |
| Insulation resistance | > 500 MΩ |
| Nominal voltage U_N | 48 V |
| Nominal current I_N | 1.75 A |
| Contact resistance per contact pair | < 20 Ω |
| Contact resistance | > 10 mΩ (Wire – IDC) 0.005 Ω (Litz wires – IDC) |
| Transmission medium | Copper |
| Transmission characteristics (category) | CAT5 |
| Transmission speed | 1 Gbps |
| Power transmission | PoE++ |

Connection data

Connection technology

| | |
|------------------------------|---|
| Connection method | Insulation displacement connection |
| Connection cross section AWG | 26 ... 23 (solid) 26 ... 23 (flexible) |
| Conductor cross section | 0.14 mm ² ... 0.25 mm ² (solid) 0.14 mm ² ... 0.25 mm ² (flexible) |

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector



1658008

<https://www.phoenixcontact.com/us/products/1658008>

| | |
|----------------------------------|----------------------------------|
| Connection in acc. with standard | In accordance with IEC 60603-7-1 |
| Cable outlet, angle | 180 |

Dimensions

| | |
|--------|----------|
| Width | 14 mm |
| Height | 14.6 mm |
| Length | 55.85 mm |

Material specifications

| | |
|--|---------|
| Color | black |
| Material | Plastic |
| Flammability rating according to UL 94 | V0 |
| Cable seal material | NBR |
| Contact material | CuSn |
| Contact surface material | Au/Ni |
| Contact carrier material | PC |
| O-ring material | FPM |
| Locking latch material | PC |
| Material for screw connection | PA |
| Housing material | Plastic |

Cable/line

| | |
|-----------------------------|----------------------|
| External cable diameter () | 4.5 mm ... 8 mm |
| External cable diameter | 4.5 mm ... 8 mm |
| Cable cross section | 0.14 mm ² |
| Test voltage Core/Core | 1000 V |
| Test voltage Core/Shield | 1500.00 V |
| Halogen-free | no |

Mechanical properties

Mechanical data

| | |
|-------------------------------------|-----------|
| Insertion/withdrawal cycles | ≥ 1000 |
| Insertion force per signal contact | < 20.00 N |
| Extraction force per signal contact | < 20 N |

Environmental and real-life conditions

Test specification

| | |
|---------------|------------------------|
| Type of test | Vibration test |
| Specification | IEC 60068-2-6 |
| Frequency | 10-500 Hz |
| Sweep speed | 1 octave/min |
| Amplitude | 0.35 mm |
| Acceleration | 50.00 m/s ² |
| Test duration | 20.00 s |

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector



1658008

<https://www.phoenixcontact.com/us/products/1658008>

Ambient conditions

| | |
|---|------------------|
| Degree of protection | IP20 |
| | IP20 |
| Ambient temperature (operation) | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |

Mounting

| | |
|---------------|--------------------|
| Mounting type | For field assembly |
|---------------|--------------------|

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector



1658008

<https://www.phoenixcontact.com/us/products/1658008>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440101 |
| ECLASS-12.0 | 27440113 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002636 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector



1658008

<https://www.phoenixcontact.com/us/products/1658008>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com