

1658684

https://www.phoenixcontact.com/us/products/1658684

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 coupling, IP67, CAT5e, with protective cover, color: black

## Your advantages

- IP65/67
- · Including covers for protection against environmental influences

### Commercial data

Item number	1658684
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB17
Product key	ABNNAZ
Catalog page	Page 353 (C-2-2019)
GTIN	4046356163217
Weight per piece (including packing)	54.1 g
Weight per piece (excluding packing)	44.94 g
Customs tariff number	85366990
Country of origin	DE



https://www.phoenixcontact.com/us/products/1658684



### Technical data

### Product properties

Product type	Female insert
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45
No. of cable outlets	1
Number of slots	1
Housing type	Plastic sleeve housing
Shielded	no
Cable outlet	straight
Insulation characteristics	
Overvoltage category	I
Degree of pollution	1

### Electrical properties

Rated voltage (III/3)	72 V (DC)
Rated surge voltage	≥ 1 kV
Rated current	1 A
Insulation resistance	≥ 500 MΩ
Nominal voltage U <sub>N</sub>	48 V
Transmission medium	Copper
Transmission characteristics (category)	CAT5

### Connection data

### Connection technology

|--|

### **Dimensions**

Dimensional drawing	
	- 34.5 - 43
Width	43 mm
Height	36.5 mm
Length	58.9 mm

### Material specifications

Color	black
-------	-------



1658684

https://www.phoenixcontact.com/us/products/1658684

Flammability rating according to UL 94	V0
Seal material	NBR
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	Thermoplastic
Housing material	Plastic

### Mechanical properties

### Mechanical data

Insertion/withdrawal cycles	≥ 750

### Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
	IP65/IP67
Ambient temperature (operation)	-10 °C 60 °C
Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-40 °C 55 °C



1658684

https://www.phoenixcontact.com/us/products/1658684

## Classifications

UNSPSC 21.0

### **ECLASS**

ECLASS-11.0	19179090
ECLASS-12.0	19179090
ECLASS-13.0	19179090
ETIM	
ETIM 9.0	EC002608
UNSPSC	

43222600



https://www.phoenixcontact.com/us/products/1658684



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com