

# CK4,0-ED-4,00ST AG - Crimp contact



1663255

<https://www.phoenixcontact.com/us/products/1663255>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimp contact, contact diameter: 4 mm, turned, Pin, contact material: Copper alloy, contact surface: silver-plated, connection cross section: 4 mm<sup>2</sup> ... 4 mm<sup>2</sup>, AWG 12

## Commercial data

Item number	1663255
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	BF65
Product key	BF7AIE
Catalog page	Page 511 (C-2-2019)
GTIN	4017918123062
Weight per piece (including packing)	3.064 g
Weight per piece (excluding packing)	3.064 g
Customs tariff number	85366990
Country of origin	DE

# CK4,0-ED-4,00ST AG - Crimp contact



1663255

<https://www.phoenixcontact.com/us/products/1663255>

## Technical data

### Notes

General	for HC-M-02, HC-M-03, HC-M-03/04, HC-M-04, HC-Q02, HC-Q03, HC-Q04, and HC-COM-Q4/2 contact carriers
---------	---

### Mounting

Assembly instructions	The quality of a crimp connection is determined by DIN EN 60352-2.
-----------------------	--

### Product properties

Product type	Crimp contact
Type	Individual male contact
Contact material type	turned
Series	HC-M-03
	HC-M-03/04
	HC-M-04
	HC-K
	HC-M-02
	HC-HS
	HC-COM

### Connection data

Connection method	Crimp connection
Contact connection type	Pin
Connection technology	Crimp connection
Conductor cross section	4 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Connection cross section AWG	12
Stripping length of the individual wire	10 mm
Conductor cross section flexible	4 mm <sup>2</sup> ... 4 mm <sup>2</sup>

### Material specifications

Contact material	Copper alloy
Contact surface material	silver-plated

### Dimensions

#### Mechanical characteristics

Contact diameter	4 mm
------------------	------

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

### Environmental and real-life conditions

# CK4,0-ED-4,00ST AG - Crimp contact



1663255

<https://www.phoenixcontact.com/us/products/1663255>

## Ambient conditions

Ambient temperature (operation)

-40 °C ... 125 °C

# CK4,0-ED-4,00ST AG - Crimp contact



1663255

<https://www.phoenixcontact.com/us/products/1663255>

## Classifications

### ECLASS

ECLASS-11.0	27440204
ECLASS-12.0	27440204
ECLASS-13.0	27440204

### ETIM

ETIM 9.0	EC000796
----------	----------

### UNSPSC

UNSPSC 21.0	39121500
-------------	----------

# CK4,0-ED-4,00ST AG - Crimp contact



1663255

<https://www.phoenixcontact.com/us/products/1663255>

## Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)