

CK4,0-ED-2,50BU AG - Crimp contact



1663284

<https://www.phoenixcontact.com/us/products/1663284>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimp contact, contact diameter: 4 mm, turned, Socket, contact material: Copper alloy, contact surface: silver-plated, connection cross section: 2.5 mm² ... 2.5 mm², AWG 14

Commercial data

Item number	1663284
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	BF65
Product key	BF7AIE
Catalog page	Page 511 (C-2-2019)
GTIN	4017918123093
Weight per piece (including packing)	2.485 g
Weight per piece (excluding packing)	2.485 g
Customs tariff number	85366990
Country of origin	DE

CK4,0-ED-2,50BU AG - Crimp contact



1663284

<https://www.phoenixcontact.com/us/products/1663284>

Technical data

Notes

General	for HC-M-02, HC-M-03, HC-M-03/04, HC-M-04, HC-Q02, HC-Q03, HC-Q04, and HC-COM-Q4/2 contact carriers
---------	---

Mounting

Assembly instructions	The quality of a crimp connection is determined by DIN EN 60352-2.
-----------------------	--

Product properties

Product type	Crimp contact
Type	Individual female contact
Contact material type	turned
Series	HC-M-03
	HC-M-03/04
	HC-M-04
	HC-K
	HC-M-02
	HC-HS
	HC-COM

Connection data

Connection method	Crimp connection
Contact connection type	Socket
Connection technology	Crimp connection
Conductor cross section	2.5 mm ² ... 2.5 mm ²
Connection cross section AWG	14
Stripping length of the individual wire	9 mm (9.6 mm (4-6 mm ²))
Conductor cross section flexible	2.5 mm ² ... 2.5 mm ²

Material specifications

Contact material	Copper alloy
Contact surface material	silver-plated

Dimensions

Mechanical characteristics

Contact diameter	4 mm
------------------	------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

CK4,0-ED-2,50BU AG - Crimp contact



1663284

<https://www.phoenixcontact.com/us/products/1663284>

Ambient conditions

Ambient temperature (operation)

-40 °C ... 125 °C

CK4,0-ED-2,50BU AG - Crimp contact



1663284

<https://www.phoenixcontact.com/us/products/1663284>

Classifications

ECLASS

ECLASS-11.0	27440204
ECLASS-12.0	27440204
ECLASS-13.0	27440204

ETIM

ETIM 9.0	EC000796
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

CK4,0-ED-2,50BU AG - Crimp contact



1663284

<https://www.phoenixcontact.com/us/products/1663284>

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com