

VS-15-BU-DSUB-3P - D-SUB contact support



1688214

<https://www.phoenixcontact.com/us/products/1688214>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact carrier, shell size 2, accommodation for three combined contacts, type of contact socket, straight, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-15-...



Your advantages

- Compatible with IP67 sleeve housing and panel-mount frame
- Easy assembly

Commercial data

Item number	1688214
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAB
Catalog page	Page 214 (C-2-2013)
GTIN	4017918179618
Weight per piece (including packing)	11.44 g
Weight per piece (excluding packing)	11.44 g
Customs tariff number	85366990
Country of origin	DE

VS-15-BU-DSUB-3P - D-SUB contact support



1688214

<https://www.phoenixcontact.com/us/products/1688214>

Technical data

Notes

General	The contacts must be ordered separately since they are not included in the scope of supply of the contact carriers.
---------	---

Product properties

Type	D-SUB
Product type	Female insert
Number of positions	3
Connection profile	D-SUB
Number of slots	1
Type	Socket
Shielded	yes

Electrical properties


Transmission medium	Copper
---------------------	--------

Connection data

Connection technology

Connection method	Wave soldering contacts
-------------------	-------------------------

Dimensions

Dimensional drawing	
Width	12.6 mm
Height	12.93 mm
Length	39.52 mm

Material specifications

Flammability rating according to UL 94	V0
Housing surface material	metal-plated
Contact surface material	Gold
Contact carrier material	PBTP
Housing material	Metal

Mechanical properties

Mechanical data

VS-15-BU-DSUB-3P - D-SUB contact support



1688214

<https://www.phoenixcontact.com/us/products/1688214>

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

Mounting

Mounting type	Screw mounting
---------------	----------------

VS-15-BU-DSUB-3P - D-SUB contact support



1688214

<https://www.phoenixcontact.com/us/products/1688214>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

ETIM

ETIM 9.0	EC003557
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-15-BU-DSUB-3P - D-SUB contact support



1688214

<https://www.phoenixcontact.com/us/products/1688214>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com