

VS-09-ST-DSUB-CD-B - D-SUB contact support



1688858

<https://www.phoenixcontact.com/us/products/1688858>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact carrier, shell size 1, for nine signal contacts, type of contact pin, for crimp contacts, straight, fixing with 3 mm hole, for panel mounting frame and sleeve housing VS-09-...



Your advantages

- D-SUB 9 connection
- Compatible with IP67 sleeve housing and panel-mount frame
- Easy assembly

Commercial data

Item number	1688858
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAA
Catalog page	Page 212 (C-2-2013)
GTIN	4017918822989
Weight per piece (including packing)	9.74 g
Weight per piece (excluding packing)	9.74 g
Customs tariff number	85366990
Country of origin	DE

VS-09-ST-DSUB-CD-B - D-SUB contact support



1688858

<https://www.phoenixcontact.com/us/products/1688858>

Technical data

Notes

General	Test voltage only in combination with crimp contact, Item No.: 1418786.
---------	---

Product properties

Type	D-SUB
Product type	Male insert
Number of positions	9
Connection profile	D-SUB 9
Type	Male
Shielded	no

Insulation characteristics

Overvoltage category	III
Degree of pollution	2


Electrical properties

Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1500 V
Transmission medium	Copper

Connection data

Connection method	Crimp connection
-------------------	------------------

Dimensions

Dimensional drawing	
Width	18 mm
Height	12.93 mm
Length	31.2 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact carrier material	Glass-fiber reinforced thermoplastics, UL 94 V0

VS-09-ST-DSUB-CD-B - D-SUB contact support



1688858

<https://www.phoenixcontact.com/us/products/1688858>

Housing material	Steel, tin-plated
------------------	-------------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
Insertion force per signal contact	≤ 3.40 N

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-55 °C ... 130 °C
---------------------------------	-------------------

Mounting

Mounting type	Hole
---------------	------

1688858

<https://www.phoenixcontact.com/us/products/1688858>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

ETIM

ETIM 9.0	EC003557
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-09-ST-DSUB-CD-B - D-SUB contact support



1688858

<https://www.phoenixcontact.com/us/products/1688858>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com