

VS-25-ST-DSUB-5P - D-SUB contact support



1689970

<https://www.phoenixcontact.com/us/products/1689970>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact carrier, shell size 3, accommodation for five combined contacts, type of contact pin, straight, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-25-...



Your advantages

- Compatible with IP67 sleeve housing and panel-mount frame
- Easy assembly

Commercial data

Item number	1689970
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAA
Catalog page	Page 214 (C-2-2013)
GTIN	4017918914370
Weight per piece (including packing)	13.28 g
Weight per piece (excluding packing)	7.59 g
Customs tariff number	85366990
Country of origin	DE

VS-25-ST-DSUB-5P - D-SUB contact support



1689970

<https://www.phoenixcontact.com/us/products/1689970>

Technical data

Notes

General	The contacts must be ordered separately since they are not included in the scope of supply of the contact carriers.
---------	---

Product properties

Type	D-SUB
Product type	Male insert
Number of positions	5
Connection profile	D-SUB
Type	Male
Shielded	no


Electrical properties

Transmission medium	Copper
---------------------	--------

Connection data

Connection method	D-SUB
-------------------	-------

Dimensions

Dimensional drawing	
Width	12.4 mm
Height	12.93 mm
Length	53.42 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	PBTP
Housing material	Steel, yellow chromated

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

VS-25-ST-DSUB-5P - D-SUB contact support



1689970

<https://www.phoenixcontact.com/us/products/1689970>

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

Mounting

Mounting type	Hole
---------------	------

VS-25-ST-DSUB-5P - D-SUB contact support



1689970

<https://www.phoenixcontact.com/us/products/1689970>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

ETIM

ETIM 9.0	EC003557
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-25-ST-DSUB-5P - D-SUB contact support



1689970
<https://www.phoenixcontact.com/us/products/1689970>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com