

GKM 2 GY - Cable marker carrier



1750485

<https://www.phoenixcontact.com/us/products/1750485>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marker carrier, gray, unlabeled, mounting type: clip on, cable diameter range: 4.8 ... 11 mm, lettering field size: 20 x 8 mm

Your advantages

- SS-ZB ..., UC-TM ... or ZB ... can be used for labeling purposes
- The conductor marker is attached directly to a conductor

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1750485 |
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Sales key | BG12 |
| Product key | BG231A |
| Catalog page | Page 243 (C-3-2019) |
| GTIN | 4017918028282 |
| Weight per piece (including packing) | 2.66 g |
| Weight per piece (excluding packing) | 2.46 g |
| Customs tariff number | 39269097 |
| Country of origin | DE |

GKM 2 GY - Cable marker carrier



1750485

<https://www.phoenixcontact.com/us/products/1750485>

Technical data

Product properties

| | |
|--------------|----------------------|
| Product type | Marker carrier cable |
| Type | Mounting set |

Dimensions

| | |
|--------|-------|
| Width | 9 mm |
| Length | 20 mm |

External dimensions

| | |
|------------------------|------------------|
| Outside diameter | 4.8 mm ... 11 mm |
| External diameter min. | 4.8 mm |
| External diameter max. | 11 mm |

Material specifications

| | |
|--|--------------------------------|
| Color | gray |
| Material | PA/ABS |
| Flammability rating according to UL 94 | V2 |
| Components | free from silicone and halogen |

Cable/line

| | |
|-------------------------|------------------|
| External cable diameter | 4.8 mm ... 11 mm |
|-------------------------|------------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |

Mounting

| | |
|---------------|---------|
| Mounting type | clip on |
|---------------|---------|

GKM 2 GY - Cable marker carrier



1750485

<https://www.phoenixcontact.com/us/products/1750485>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27281105 |
| ECLASS-12.0 | 27281105 |
| ECLASS-13.0 | 27281105 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001530 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com