VC-K-KV-PG21-2X4,5/1X13 - Cable gland

1885282

https://www.phoenixcontact.com/us/products/1885282

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Half screw connection Pg21, made of plastic, consisting of rubber seal with several holes (2 x 4. 5 mm/1 x 13 mm) and a pressure screw, for cable screw connection thread VC-M-KV-PG21.....

Commercial data

Item number	1885282
Packing unit	5 pc
Minimum order quantity	5 pc
Note	Made to order (non-returnable)
Sales key	AB01
Product key	ABLAZA
Catalog page	Page 47 (C-2-2013)
GTIN	4017918176396
Weight per piece (including packing)	16.7 g
Weight per piece (excluding packing)	15.5 g
Customs tariff number	39269097
Country of origin	PL

PHŒNIX

https://www.phoenixcontact.com/us/products/1885282



Technical data

Notes

Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	WARNING: Only electrically qualified personnel may install a operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicate that only personnel familiar with electrical engineering are allowed to install and operate the product.
	 The products are suitable for applications in plant, controller, and electrical device engineering.
	When operating the connectors in outdoor applications, they must be separately protected against environmental influences
	Assembled products may not be manipulated or improperly opened.
	 Only use mating connectors that are specified in the technica data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	 When using the product in direct connection with third-party manufacturers, the user is responsible.
	 For operating voltages > 50 V AC, conductive connector housings must be grounded
	 Ensure that the protective or functional ground has been properly connected.
	VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1. are applicable when combining several circuits in a cable and/o connector
	Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product
	Only use tools recommended by Phoenix Contact
	 The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
	 Use a protective cap to protect connectors that are not in use The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	Operate the connector only when it is fully plugged in.
	 Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the



https://www.phoenixcontact.com/us/products/1885282

standards.
 Observe the minimum bending radius of the cable. Lay the cable without twisting it.
• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Product type	Multiple screw connection
Product family	VARIOCON
No. of conductors	3
Type of the screw connection	Half screw connection
Shielded	no

Connection data

Dimensions

Dimensional drawing

	PG21	
5		
M32x1,5		
7		-
	35	33

4 mm ... 4.5 mm (Cable 1)

Width	36.5 mm
Height	36.5 mm
Length	31 mm
Wrench size, union nut	33 mm
Thread type on seal side	Pg21

Material specifications

Color	gray
Material	PVC
	Polycarbonate
Seal material	TPE
Material for screw connection	Plastic

Cable/line

External cable diameter (Cable 1)	4 mm 4.5 mm (Cable 1)
-----------------------------------	-----------------------

Mechanical properties

Mechanical data		
	Type of the screw connection	Half screw connection

Environmental and real-life conditions



https://www.phoenixcontact.com/us/products/1885282

Ambient conditions	
Degree of protection	IP65
	IP65
Ambient temperature (operation)	-20 °C 100 °C

https://www.phoenixcontact.com/us/products/1885282



Classifications

ECLASS

ECLASS-12.0 27140801	ECLASS-11.0	27144432
	ECLASS-12.0	27140801
ECLASS-13.0 27140801	ECLASS-13.0	27140801

ETIM

	ETIM 9.0	EC000441	
UNSPSC			
	UNSPSC 21.0	39121300	



https://www.phoenixcontact.com/us/products/1885282

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com