FBSK 10-7,5 - Plug-in bridge

1928385

https://www.phoenixcontact.com/us/products/1928385

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bridge, fully insulated, pitch 7.5 mm, 10-pos.

Commercial data

Item number	1928385
Packing unit	50 pc
Minimum order quantity	50 pc
Note	Made to order (non-returnable)
Sales key	AA18
Product key	AARZFD
Catalog page	Page 830 (C-1-2013)
GTIN	4017918606619
Weight per piece (including packing)	10.06 g
Weight per piece (excluding packing)	10.06 g
Customs tariff number	85366990
Country of origin	PL

FBSK 10-7,5 - Plug-in bridge

1928385

https://www.phoenixcontact.com/us/products/1928385



Technical data

Product properties

Product line	COMBICON Terminals Special
	COmbicon Terminais Special
Product type	Bridge
Product family	FBSK
Number of positions	10
Pitch	7.5 mm
Number of connections	10
Number of rows	1
Number of potentials	10
lectrical properties	
Degree of pollution	3
imensions	
Pitch	7.5 mm
Material data - contact	
Note	WEEE/RoHS-compliant, free of whiskers according to IEC
	60068-2-82/JEDEC JESD 201
Contact material	
Contact material	60068-2-82/JEDEC JESD 201
Contact material Material data - housing	60068-2-82/JEDEC JESD 201 Cu alloy
Contact material Material data - housing Color (Housing)	60068-2-82/JEDEC JESD 201 Cu alloy red (3001)
Contact material Material data - housing Color (Housing) Insulating material	60068-2-82/JEDEC JESD 201 Cu alloy red (3001)
Contact material Material data - housing Color (Housing) Insulating material Insulating material group	60068-2-82/JEDEC JESD 201 Cu alloy red (3001) PA I
Contact material Material data - housing Color (Housing) Insulating material Insulating material group CTI according to IEC 60112	60068-2-82/JEDEC JESD 201 Cu alloy red (3001) PA I 600
Contact material Material data - housing Color (Housing) Insulating material Insulating material group CTI according to IEC 60112 Flammability rating according to UL 94	60068-2-82/JEDEC JESD 201 Cu alloy red (3001) PA I 600 V0

Connector

. 10-2

Connection 1			
Insulating material	PA		
CTI according to IEC 60112	600		

FBSK 10-7,5 - Plug-in bridge

1928385

https://www.phoenixcontact.com/us/products/1928385



Classifications

ECLASS

	ECLASS-11.0	27460406
	ECLASS-12.0	27460406
	ECLASS-13.0	27460406
ET	IM	

ETIM 9.0 EC002943 UNSPSC 39121400



1928385

https://www.phoenixcontact.com/us/products/1928385



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com