

1954362

https://www.phoenixcontact.com/us/products/1954362

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

HT coding section, prior to the reflow soldering process it is inserted into the recess on the header, made from high-temperature-resistant beige insulation material



Commercial data

Item number	1954362
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AA08
Product key	AAHZBC
Catalog page	Page 446 (CC-2007)
GTIN	4017918897574
Weight per piece (including packing)	0.787 g
Weight per piece (excluding packing)	0.58 g
Customs tariff number	39269097
Country of origin	DE



1954362

https://www.phoenixcontact.com/us/products/1954362

Technical data

Product properties

Product type	Coding element
Product family	Coding
Number of positions	1
Pitch	0 mm

Mounting

Processing notes

Process	Reflow/wave soldering
Moisture Sensitive Level	MSL 3
Classification temperature T _c	260 °C
Solder cycles in the reflow	3

Material specifications

Color (Housing)	transparent
-----------------	-------------

Dimensions

Notes

General	The packing unit (PU) refers to individual coding sections. Six
	coding sections are located on a coding star.



1954362

https://www.phoenixcontact.com/us/products/1954362

Classifications

ECLASS

	ECLASS-12.0	27460401
	ECLASS-13.0	27460401
	ECLASS-11.0	27460401
ETIM		
	ETIM 9.0	EC002943
UNSPSC		
	UNSPSC 21.0	39121400



https://www.phoenixcontact.com/us/products/1954362



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com