

FBSK 4-10/ZFKDS 10 - Plug-in bridge



1986660
<https://www.phoenixcontact.com/us/products/1986660>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fixed bridge, fully insulated, pitch: 10 mm, no. of positions: 4

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1986660 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Note | Made to order (non-returnable) |
| Sales key | AA18 |
| Product key | AARZFE |
| Catalog page | Page 830 (C-1-2013) |
| GTIN | 4017918973124 |
| Weight per piece (including packing) | 9.88 g |
| Weight per piece (excluding packing) | 9.682 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

FBSK 4-10/ZFKDS 10 - Plug-in bridge



1986660

<https://www.phoenixcontact.com/us/products/1986660>

Technical data

Product properties

| | |
|-----------------------|----------------------------|
| Product line | COMBICON Terminals Special |
| Product type | Bridge |
| Product family | FBSK |
| Number of positions | 4 |
| Pitch | 10 mm |
| Number of connections | 4 |
| Number of rows | 1 |
| Number of potentials | 4 |

Electrical properties

| | |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

Dimensions

| | |
|-------|-------|
| Pitch | 10 mm |
|-------|-------|

Material specifications

Material data - contact

| | |
|------------------|--|
| Note | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material | Cu alloy |

Material data - housing

| | |
|---|------------|
| Color (Housing) | red (3001) |
| Insulating material | PA |
| Insulating material group | I |
| CTI according to IEC 60112 | 600 |
| Flammability rating according to UL 94 | V0 |
| Glow wire flammability index GWFI according to EN 60695-2-12 | 850 |
| Glow wire ignition temperature GWIT according to EN 60695-2-13 | 775 |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C |

Connector

Connection 1

| | |
|----------------------------|-----|
| Insulating material | PA |
| CTI according to IEC 60112 | 600 |

FBSK 4-10/ZFKDS 10 - Plug-in bridge



1986660

<https://www.phoenixcontact.com/us/products/1986660>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27460406 |
| ECLASS-12.0 | 27460406 |
| ECLASS-13.0 | 27460406 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002943 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

FBSK 4-10/ZFKDS 10 - Plug-in bridge



1986660

<https://www.phoenixcontact.com/us/products/1986660>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com