

2200484

https://www.phoenixcontact.com/us/products/2200484

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PCB connector, nominal cross section: 2.5 mm², color: black, nominal current: 16 A, rated voltage (III/2): 320 V, contact surface: Tin, contact connection type: Socket, number of rows: 1, number of positions: 2, product range: MSTBT 2,5 HC/..-STP, pitch: 5 mm, connection method: Screw connection with tension sleeve, conductor/PCB connection direction: 0 °, locking clip: Locking clip, plug-in system: COMBICON MSTB 2,5 HC, locking: without, mounting: without

### Your advantages

- · Orthogonal plug-in screw connection
- · Internationally recognized and proven screw connection

### Commercial data

Item number	2200484
Packing unit	50 pc
Minimum order quantity	1 pc
Product key	ACHADB
GTIN	4046356656962
Weight per piece (including packing)	3.498 g
Weight per piece (excluding packing)	3.498 g
Country of origin	DE



2200484

https://www.phoenixcontact.com/us/products/2200484

### Technical data

### Product properties

Туре	Standard
Product line	COMBICON Connectors M
Product type	PCB connector
Product family	MSTBT 2,5 HC/STP
Number of positions	2
Pitch	5 mm
Number of rows	1
Mounting flange	without

### Electrical properties

Nominal current I <sub>N</sub>	16 A
Nominal voltage $U_N$	250 V
Degree of pollution	3
Contact resistance	1.2 mΩ
Rated voltage (III/3)	250 V
Rated surge voltage (III/3)	4 kV
Rated voltage (III/2)	320 V
Rated surge voltage (III/2)	4 kV
Rated voltage (II/2)	630 V
Rated surge voltage (II/2)	4 kV

### Connection data

### Connection technology

Туре	Standard
Connector system	COMBICON MSTB 2,5 HC
Nominal cross section	2.5 mm²
Contact connection type	Socket

### Interlock

Locking type	without
Mounting flange	without

### Conductor connection

Connection method	Screw connection with tension sleeve
Conductor/PCB connection direction	0°
Conductor cross section rigid	0.2 mm² 2.5 mm²
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section AWG	24 12
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm² 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.25 mm² 2.5 mm²



2200484

https://www.phoenixcontact.com/us/products/2200484

2 conductors with same cross section, solid	0.2 mm² 1 mm²
2 conductors with same cross section, flexible	0.2 mm² 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm² 1 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
Cylindrical gauge a x b / diameter	2.8 mm x 2.0 mm / 2.4 mm
Stripping length	7 mm
Tightening torque	0.5 Nm 0.6 Nm

### Material specifications

### Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	hot-dip tin-plated
Metal surface terminal point (top layer)	Tin (4 - 8 μm Sn)
Metal surface contact area (top layer)	Tin (4 - 8 μm Sn)

#### Material data - housing

Color (Housing)	black (9005)
Insulating material	PA
Insulating material group	I
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0
Glow wire flammability index GWFI according to EN 60695-2-12	850
Glow wire ignition temperature GWIT according to EN 60695-2-13	775
Temperature for the ball pressure test according to EN 60695-10-2	125 °C

### Dimensions

Dimensional drawing	h
Pitch	5 mm
Width [w]	10 mm
Height [h]	15 mm
Length [I]	18.1 mm

### Notes

Notes on operation	In accordance with IEC 61984, COMBICON connectors have no switching power (COC). During designated use, they must not be
	plugged in or disconnected when carrying voltage or under load.



2200484

https://www.phoenixcontact.com/us/products/2200484

Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	<ul> <li>WARNING: Commission properly functioning products only.</li> <li>The products must be regularly inspected for damage.</li> <li>Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li> </ul>
	<ul> <li>WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.</li> </ul>
	<ul> <li>The item is intended to be an unencapsulated plug for installation in a housing.</li> </ul>
	Operate the connector only when it is fully plugged in.
Mechanical tests  Test for conductor damage and slackening	
Specification	IEC 60999-1:1999-11
Result	Test passed
	<u> </u>
Pull-out test	IFO 00000 4 4000 44
Specification	IEC 60999-1:1999-11
Conductor cross section/conductor type/tractive force setpoint/actual value	0.2 mm² / solid / > 10 N
Corporiti doctula varido	0.2 mm² / flexible / > 10 N 2.5 mm² / solid / > 50 N
	2.5 mm² / flexible / > 50 N
	2.6 Hill / Hoxidie / * Go IV
Insertion and withdrawal forces	
Result	Test passed
No. of cycles	25
Insertion strength per pos. approx.	11 N
Withdraw strength per pos. approx.	7 N
Torque test	
Specification	IEC 60999-1:1999-11
Resistance of inscriptions	
Specification	IEC 60068-2-70:1995-12
Result	Test passed
Polarization and coding	
Specification	IEC 60512-13-5:2006-02
Result	Test passed
Visual inspection	



2200484

https://www.phoenixcontact.com/us/products/2200484

Specification	IEC 60512-1-1:2002-02	
Result	Test passed	
Dimension check		
Dimension check		
Dimension check Specification	IEC 60512-1-2:2002-02	

### Environmental and real-life conditions

#### Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 Hz 60.1 Hz)
Sweep speed	5g (60.1 Hz 150 Hz)
Test duration per axis	2.5 h

### **Durability test**

Specification	IEC 60512-9-1:2010-03
Impulse withstand voltage at sea level	4.8 kV
Contact resistance R <sub>1</sub>	1.2 mΩ
Contact resistance R <sub>2</sub>	1.23 mΩ
Insertion/withdrawal cycles	25
Insulation resistance, neighboring positions	> 21 TΩ

#### Climatic test

Specification	ISO 6988:1985-02
Corrosive stress	$1.0~\mathrm{dm^3~SO_2}$ on $300~\mathrm{dm^3/40~^\circ C/3}$ cycles
Thermal stress	100 °C/168 h
Power-frequency withstand voltage	3.1 kV

#### Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (dependent on the derating curve)
Ambient temperature (storage/transport)	-40 °C 55 °C
Relative humidity (storage/transport)	30 % 70 %
Ambient temperature (assembly)	-5 °C 100 °C

### Electrical tests

#### Thermal test | Test group C

, 5 ,	
Specification	IEC 60512-5-1:2002-02
Tested number of positions	4
Insulation resistance	
Specification	IEC 60512-3-1:2002-02

> 21 TΩ

Air clearances and creepage distances |

Insulation resistance, neighboring positions



2200484

https://www.phoenixcontact.com/us/products/2200484

Specification	IEC 60664-1:2007-04
Insulating material group	l I
Comparative tracking index (IEC 60112)	CTI 600
Rated insulation voltage (III/3)	250 V
Rated surge voltage (III/3)	4 kV
minimum clearance value - non-homogenous field (III/3)	3 mm
minimum creepage distance (III/3)	3.2 mm
Rated insulation voltage (III/2)	320 V
Rated surge voltage (III/2)	4 kV
minimum clearance value - non-homogenous field (III/2)	3 mm
minimum creepage distance (III/2)	1.6 mm
Rated insulation voltage (II/2)	630 V
Rated surge voltage (II/2)	4 kV
minimum clearance value - non-homogenous field (II/2)	3 mm
minimum creepage distance (II/2)	3.2 mm



2200484

https://www.phoenixcontact.com/us/products/2200484

### Classifications

### **ECLASS**

	ECLASS-11.0	27460202
	ECLASS-12.0	27460202
	ECLASS-13.0	27460202
ET	TIM	
	ETIM 9.0	EC002638
UN	ISPSC	
	UNSPSC 21.0	39121400



2200484

https://www.phoenixcontact.com/us/products/2200484

### Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com