

2200537

https://www.phoenixcontact.com/us/products/2200537

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing, Lower housing part with metal foot catch, with 3 FE contacts, tall design, with vents, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, color: light grey (similar RAL 7035), cross connection: integrated bus connector, number of positions cross connector: 5+2, Bus connector: 5 parallel contacts, 2 serial contacts

Your advantages

- · Tool-free mounting
- · Available in overall widths from 12.5 mm to 90 mm, modular extension possible
- · Flammability rating V0 in accordance with UL 94
- · Variety of connection technology
- · Can be mounted on the DIN rail
- With integrated or DIN-rail-mountable bus connector as an option

Commercial data

Item number	2200537
Packing unit	10 pc
Minimum order quantity	1 pc
Product key	ACHAAB
Catalog page	Page 665 (C-1-2013)
GTIN	4046356608039
Weight per piece (including packing)	105.6 g
Weight per piece (excluding packing)	105.6 g
Country of origin	DE



2200537

https://www.phoenixcontact.com/us/products/2200537

Technical data

Notes

General	Refer to the data sheet for the range in the download area.
General	Material of contact pads for bus connector, galvanic gold (hard gold)

Product properties

Product type	Enclosure bottom part
Housing series	ME
Product family	MEUT/FE BUS/ 5+2
Туре	Lower housing part with metal foot catch, with 3 FE contacts, tall design
Housing type	DIN rail housing
Ventilation openings present	yes

Dimensions

Dimensional drawing	h
Width	67.8 mm
Height	99 mm
Depth	107.3 mm
Depth from top edge of DIN rail	100.7 mm
Depth from top edge of DIN rail to support point on upper part	68.5 mm
PCB design	

Material specifications

PCB thickness

Color (Housing)	light grey (RAL 7035)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Surface characteristics	untreated
Housing material	Polyamide

1.4 mm ... 1.8 mm

Environmental and real-life conditions

Power dissipation single housing for 20 °C

Ambient temperature	20 °C



2200537

https://www.phoenixcontact.com/us/products/2200537

Reduction factor	1
Mounting position	vertical
Power dissipation	9.1 W
Device discipation simple benefits for 20 °C	
Power dissipation single housing for 30 °C	30 °C
Ambient temperature	
Reduction factor	0.91 vertical
Mounting position	8.3 W
Power dissipation	0.3 VV
Power dissipation single housing for 40 °C	
Ambient temperature	40 °C
Reduction factor	0.81
Mounting position	vertical
Power dissipation	7.4 W
Downer discination single beginning for EO °C	
Power dissipation single housing for 50 °C	50 °C
Ambient temperature Reduction factor	0.7
	vertical
Mounting position	6.4 W
Power dissipation	0.4 VV
Power dissipation single housing for 60 °C	
Ambient temperature	60 °C
Reduction factor	0.57
Mounting position	vertical
Power dissipation	5.2 W
Power dissipation single housing for 70 °C	
Ambient temperature	70 °C
Reduction factor	0.49
Mounting position	vertical
Power dissipation	4.6 W
1 ower dissipation	7.0 11
Vibration test	
Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 Hz 58.1 Hz)
Acceleration	2g (58.1 Hz 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis
Glow-wire test	
Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s



2200537

https://www.phoenixcontact.com/us/products/2200537

Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20 N
echanical strength / tumbling barrel	
Specification	IEC 60998-1:2002-12
Height of fall	50 cm
Frequency	10
hocks	
Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
egree of protection (IP code) Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
mbient conditions	
Max. IP code to attain	IP20
	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (operation)	` . • · · · ·
Ambient temperature (operation) Ambient temperature (storage/transport)	-40 °C 55 °C
Ambient temperature (storage/transport)	-40 °C 55 °C
Ambient temperature (storage/transport) Ambient temperature (assembly)	-40 °C 55 °C -5 °C 100 °C
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport)	-40 °C 55 °C -5 °C 100 °C
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport)	-40 °C 55 °C -5 °C 100 °C 80 %
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport) 3 data Number of PCB holders	-40 °C 55 °C -5 °C 100 °C 80 %
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport) 3 data Number of PCB holders Type of PCB mount Thickness of the PCB	-40 °C 55 °C -5 °C 100 °C 80 % 3 Insertion (optional latching by PCB stop)
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport) 3 data Number of PCB holders Type of PCB mount Thickness of the PCB	-40 °C 55 °C -5 °C 100 °C 80 % 3 Insertion (optional latching by PCB stop) 1.4 mm 1.8 mm
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport) B data Number of PCB holders Type of PCB mount Thickness of the PCB unting Mounting type	-40 °C 55 °C -5 °C 100 °C 80 % 3 Insertion (optional latching by PCB stop) 1.4 mm 1.8 mm DIN rail mounting
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport) 3 data Number of PCB holders Type of PCB mount Thickness of the PCB unting Mounting type Mounting position	-40 °C 55 °C -5 °C 100 °C 80 % 3 Insertion (optional latching by PCB stop) 1.4 mm 1.8 mm
Ambient temperature (storage/transport) Ambient temperature (assembly) Relative humidity (storage/transport) B data Number of PCB holders Type of PCB mount Thickness of the PCB unting Mounting type	-40 °C 55 °C -5 °C 100 °C 80 % 3 Insertion (optional latching by PCB stop) 1.4 mm 1.8 mm DIN rail mounting



2200537

https://www.phoenixcontact.com/us/products/2200537

Classifications

ECLASS

	ECLASS-11.0	27182702
	ECLASS-13.0	27190601
ETIM		
	ETIM 9.0	EC001031
UNSPSC		
	UNSPSC 21.0	31261500



2200537

https://www.phoenixcontact.com/us/products/2200537

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com