

UM-ALU 4-100,5 COVER AL - Lateral element



2200951

<https://www.phoenixcontact.com/us/products/2200951>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Press-drawn section housings, Screw mounting, Side elements (left and right) incl. snap-on foot and screws for basic profile, width: 105.4 mm, height: 2 mm, depth: 31 mm



Your advantages

- Aluminum extruded profile
- Variety of connection technology
- Can be mounted on the DIN rail
- Available in lengths from 42.5 mm ... 990 mm, can be cut to any length
- Available in overall widths of 75 mm and 105 mm
- EMC protection

Commercial data

Item number	2200951
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AC14
Product key	ACHDFA
Catalog page	Page 744 (C-1-2013)
GTIN	4046356716536
Weight per piece (including packing)	39.2 g
Weight per piece (excluding packing)	38.5 g
Customs tariff number	76161000
Country of origin	DE

UM-ALU 4-100,5 COVER AL - Lateral element



2200951

<https://www.phoenixcontact.com/us/products/2200951>

Technical data

Product properties

Product type	Panel mounting base side part
Housing series	UM-ALU
Product family	UM-ALU 4-100,5
Type	Side elements (left and right) incl. snap-on foot and screws for basic profile
Housing type	Press-drawn section housings
Ventilation openings present	no

Dimensions

Width	105.4 mm
Height	2 mm
Depth	31 mm

Material specifications

Color (Housing)	aluminum
Surface characteristics	anodized
Housing material	Aluminum

Environmental and real-life conditions

Ambient conditions

Max. IP code to attain	IP40
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 100 °C

Mounting

Mounting type	Screw mounting
Tightening torque / speed	Screw connection with the basic profile: 0.8 Nm-1 Nm / rpm- rpm

Packaging specifications

Type of packaging	packed in cardboard
Outer packaging type	Carton

UM-ALU 4-100,5 COVER AL - Lateral element



2200951

<https://www.phoenixcontact.com/us/products/2200951>

Classifications

ECLASS

ECLASS-11.0	27182701
ECLASS-13.0	27190602

ETIM

ETIM 9.0	EC002779
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

UM-ALU 4-100,5 COVER AL - Lateral element



2200951

<https://www.phoenixcontact.com/us/products/2200951>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com